

# ColorSpec Acrylic Clear Coat 1 Litre

## Motor Active

Chemwatch: 40-6489

Version No: 3.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 26/10/2017

Print Date: 26/10/2017

L.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | ColorSpec Acrylic Clear Coat 1 Litre   |
| Synonyms                      | Product Code: CSAC1L   |
| Proper shipping name          | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Other means of identification | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions.<br>The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.<br>Automotive refinish. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

|                         |   |
|-------------------------|---|
| Registered company name | Motor Active  |
| Address                 | 35 Slough Business Park, Holker Street Silverwater NSW 2128 Australia |
| Telephone               | +61 2 9737 9422 1800 350 622  |
| Fax                     | +61 2 9737 9414   |
| Website                 | www.motoractive.com.au  |
| Email                   | andrew.spira@motoractive.com.au                                       |

### Emergency telephone number

|                                   |   |
|-----------------------------------|---|
| Association / Organisation        | MotorActive   |
| Emergency telephone numbers       | +61 2 9737 9422 (For General Information Monday to Friday 8:30am to 5:pm) |
| Other emergency telephone numbers | 13 11 26 (In Case of Emergency contact: Poison Information Hotline)       |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code.

#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 3   | 4   |
| Toxicity     | 2   | 3   |
| Body Contact | 3   | 4   |
| Reactivity   | 1   | 2   |
| Chronic      | 3   | 4   |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

|                    |  |
|--------------------|--|
| Poisons Schedule   | S5   |
| Classification [1] | Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Reproductive Toxicity Category 1B, Specific target organ toxicity - single exposure Category 3 (narcotic effects), Specific target organ toxicity - repeated exposure Category 2, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2 |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI   |

### Label elements

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

SIGNAL WORD **DANGER**

### Hazard statement(s)

|      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
|------|-------------------------------------|

Continued...

|      |  |
|------|--|
| H302 | Harmful if swallowed.  |
| H332 | Harmful if inhaled.  |
| H315 | Causes skin irritation.  |
| H318 | Causes serious eye damage.   |
| H360 | May damage fertility or the unborn child.                          |
| H336 | May cause drowsiness or dizziness.                                 |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects.                   |

**Supplementary statement(s)**

Not Applicable

**CLP classification (additional)**

Not Applicable

**Precautionary statement(s) Prevention**

|      |   |
|------|---|
| P201 | Obtain special instructions before use.   |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.                |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray.                                  |
| P271 | Use only outdoors or in a well-ventilated area.                                   |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.        |
| P281 | Use personal protective equipment as required.                                    |
| P240 | Ground/bond container and receiving equipment.                                    |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| P242 | Use only non-sparking tools.  |
| P243 | Take precautionary measures against static discharge.                             |
| P270 | Do not eat, drink or smoke when using this product.                               |
| P273 | Avoid release to the environment.   |

**Precautionary statement(s) Response**

|                |  |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P310           | Immediately call a POISON CENTER or doctor/physician.  |
| P362           | Take off contaminated clothing and wash before reuse.  |
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam for extinction.   |
| P391           | Collect spillage.  |
| P301+P312      | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.                       |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |
| P330           | Rinse mouth.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |

**Precautionary statement(s) Storage**

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405      | Store locked up.                             |

**Precautionary statement(s) Disposal**

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No    | %[weight] | Name   |
|-----------|-----------|--|
| 108-88-3  | 20-40     | <u>toluene</u>   |
| 108-65-6  | <10       | <u>propylene glycol monomethyl ether acetate, alpha-isomer</u> |
| 1330-20-7 | <10       | <u>xylene</u>  |
| 67-64-1   | <10       | <u>acetone</u>   |
| 123-86-4  | <10       | <u>n-butyl acetate</u>   |

## ColorSpec Acrylic Clear Coat 1 Litre

|             |     |  |
|-------------|-----|--|
| 78-83-1     | <10 | <u>isobutanol</u>                                |
| 85-68-7     | <10 | <u>butyl benzyl phthalate</u>                    |
| 64742-95-6. | <10 | <u>naphtha petroleum, light aromatic solvent</u> |
| 763-69-9    | <10 | <u>ethyl-3-ethoxypropionate</u>                  |

## SECTION 4 FIRST AID MEASURES

## Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>  |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> </ul>      |

## Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- ▶ Gastric lavage with copious amounts of water.
- ▶ It may be beneficial to instill 60 ml of mineral oil into the stomach.
- ▶ Oxygen and artificial respiration as needed.
- ▶ Electrolyte balance: it may be useful to start 500 ml M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5]

## BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

## ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

## EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Acidosis may respond to hyperventilation and bicarbonate therapy.
- ▶ Haemodialysis might be considered in patients with severe intoxication.
- ▶ Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Continued...

## ColorSpec Acrylic Clear Coat 1 Litre

Symptomatic and supportive therapy is advised in managing patients.

Following acute or short term repeated exposures to toluene:

- ▶ Toluene is absorbed across the alveolar barrier, the blood/air mixture being 11.2/15.6 (at 37 degrees C.) The concentration of toluene, in expired breath, is of the order of 18 ppm following sustained exposure to 100 ppm. The tissue/blood proportion is 1/3 except in adipose where the proportion is 8/10.
- ▶ Metabolism by microsomal mono-oxygenation, results in the production of hippuric acid. This may be detected in the urine in amounts between 0.5 and 2.5 g/24 hr which represents, on average 0.8 gm/gm of creatinine. The biological half-life of hippuric acid is in the order of 1-2 hours.
- ▶ Primary threat to life from ingestion and/or inhalation is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (eg cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> <50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial damage has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenaline) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use.

## BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant            | Index              | Sampling Time                   | Comments |
|------------------------|--------------------|---------------------------------|----------|
| o-Cresol in urine      | 0.5 mg/L           | End of shift                    | B        |
| Hippuric acid in urine | 1.6 g/g creatinine | End of shift                    | B, NS    |
| Toluene in blood       | 0.05 mg/L          | Prior to last shift of workweek |          |

NS: Non-specific determinant; also observed after exposure to other material

B: Background levels occur in specimens collected from subjects NOT exposed

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> < 50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

## BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant                    | Index                | Sampling Time       | Comments |
|--------------------------------|----------------------|---------------------|----------|
| Methylhippu-ric acids in urine | 1.5 gm/gm creatinine | End of shift        |          |
|                                | 2 mg/min             | Last 4 hrs of shift |          |

## SECTION 5 FIREFIGHTING MEASURES

## Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**Do not** use a water jet to fight fire.

## Special hazards arising from the substrate or mixture

## Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## Advice for firefighters

## Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves in the event of a fire.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Consider evacuation (or protect in place).
- ▶ Fight fire from a safe distance, with adequate cover.
- ▶ If safe, switch off electrical equipment until vapour fire hazard removed.
- ▶ Use water delivered as a fine spray to control the fire and cool adjacent area.
- ▶ Avoid spraying water onto liquid pools.
- ▶ **Do not approach containers suspected to be hot.**
- ▶ Cool fire exposed containers with water spray from a protected location.
- ▶ If safe to do so, remove containers from path of fire.

## Fire/Explosion Hazard

- ▶ Liquid and vapour are highly flammable.
- ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.
- ▶ Vapour may travel a considerable distance to source of ignition.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:

• carbon dioxide (CO<sub>2</sub>)

• hydrogen chloride

## ColorSpec Acrylic Clear Coat 1 Litre

|                |   |
|----------------|---|
|                | phosgene<br>,<br>hydrogen fluoride<br>,<br>nitrogen oxides (NOx)<br>,<br>other pyrolysis products typical of burning organic material.<br><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions. |
| <b>HAZCHEM</b> | *3YE  |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

See section 8

## Environmental precautions

See section 12

## Methods and material for containment and cleaning up

| <b>Minor Spills</b>                | Environmental hazard - contain spillage.<br>▶ Remove all ignition sources.<br>▶ Clean up all spills immediately.<br>▶ Avoid breathing vapours and contact with skin and eyes.<br>▶ Control personal contact with the substance, by using protective equipment.<br>▶ Contain and absorb small quantities with vermiculite or other absorbent material.<br>▶ Wipe up.<br>▶ Collect residues in a flammable waste container.   |              |            |                 |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
|------------------------------------|---|--------------|------------|-----------------|------------|-------------|------------------------------------|---|--------|--------|----------|-------------------------------|---|-------|-----------|------------|----------------------------|---|--------|--------|---------|--------------------------|---|--------|--------|--------------|---------------------|---|-------|-----------|---------------|-----------------------------|---|-------|-----------|---------|------------------------------------|---|--------|------------|----------|-------------------------------|---|-------|------------|------------|----------------------------|---|--------|------------|---------|-----------------------------|---|--------|------------|------------|--------------------------------|---|--------|------------|-----------------|--------------------------|---|--------|------------|--------------|
| <b>Major Spills</b>                | Environmental hazard - contain spillage.<br>Chemical Class: ester and ethers<br>For release onto land: recommended sorbents listed in order of priority. <table border="1" data-bbox="389 972 1490 1028"> <thead> <tr> <th>SORBENT TYPE</th> <th>RANK</th> <th>APPLICATION</th> <th>COLLECTION</th> <th>LIMITATIONS</th> </tr> </thead> </table> <p>LAND SPILL - SMALL</p> <table border="1" data-bbox="389 1084 1490 1285"> <tbody> <tr> <td>cross-linked polymer - particulate</td> <td>1</td> <td>shovel</td> <td>shovel</td> <td>R, W, SS</td> </tr> <tr> <td>cross-linked polymer - pillow</td> <td>1</td> <td>throw</td> <td>pitchfork</td> <td>R, DGC, RT</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>2</td> <td>shovel</td> <td>shovel</td> <td>R, I, P</td> </tr> <tr> <td>wood fiber - particulate</td> <td>3</td> <td>shovel</td> <td>shovel</td> <td>R, W, P, DGC</td> </tr> <tr> <td>wood fiber - pillow</td> <td>3</td> <td>throw</td> <td>pitchfork</td> <td>R, P, DGC, RT</td> </tr> <tr> <td>treated wood fiber - pillow</td> <td>3</td> <td>throw</td> <td>pitchfork</td> <td>DGC, RT</td> </tr> </tbody> </table> <p>LAND SPILL - MEDIUM</p> <table border="1" data-bbox="389 1341 1490 1543"> <tbody> <tr> <td>cross-linked polymer - particulate</td> <td>1</td> <td>blower</td> <td>skiploader</td> <td>R, W, SS</td> </tr> <tr> <td>cross-linked polymer - pillow</td> <td>2</td> <td>throw</td> <td>skiploader</td> <td>R, DGC, RT</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>3</td> <td>blower</td> <td>skiploader</td> <td>R, I, P</td> </tr> <tr> <td>polypropylene - particulate</td> <td>3</td> <td>blower</td> <td>skiploader</td> <td>W, SS, DGC</td> </tr> <tr> <td>expanded mineral - particulate</td> <td>4</td> <td>blower</td> <td>skiploader</td> <td>R, I, W, P, DGC</td> </tr> <tr> <td>wood fiber - particulate</td> <td>4</td> <td>blower</td> <td>skiploader</td> <td>R, W, P, DGC</td> </tr> </tbody> </table> <p>Legend<br/>         DGC: Not effective where ground cover is dense<br/>         R: Not reusable<br/>         I: Not incinerable<br/>         P: Effectiveness reduced when rainy<br/>         RT: Not effective where terrain is rugged<br/>         SS: Not for use within environmentally sensitive sites<br/>         W: Effectiveness reduced when windy<br/>         Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;<br/>         R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Use only spark-free shovels and explosion proof equipment.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> </ul> | SORBENT TYPE | RANK       | APPLICATION     | COLLECTION | LIMITATIONS | cross-linked polymer - particulate | 1 | shovel | shovel | R, W, SS | cross-linked polymer - pillow | 1 | throw | pitchfork | R, DGC, RT | sorbent clay - particulate | 2 | shovel | shovel | R, I, P | wood fiber - particulate | 3 | shovel | shovel | R, W, P, DGC | wood fiber - pillow | 3 | throw | pitchfork | R, P, DGC, RT | treated wood fiber - pillow | 3 | throw | pitchfork | DGC, RT | cross-linked polymer - particulate | 1 | blower | skiploader | R, W, SS | cross-linked polymer - pillow | 2 | throw | skiploader | R, DGC, RT | sorbent clay - particulate | 3 | blower | skiploader | R, I, P | polypropylene - particulate | 3 | blower | skiploader | W, SS, DGC | expanded mineral - particulate | 4 | blower | skiploader | R, I, W, P, DGC | wood fiber - particulate | 4 | blower | skiploader | R, W, P, DGC |
| SORBENT TYPE                       | RANK  | APPLICATION  | COLLECTION | LIMITATIONS     |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| cross-linked polymer - particulate | 1   | shovel       | shovel     | R, W, SS        |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| cross-linked polymer - pillow      | 1   | throw        | pitchfork  | R, DGC, RT      |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| sorbent clay - particulate         | 2   | shovel       | shovel     | R, I, P         |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| wood fiber - particulate           | 3   | shovel       | shovel     | R, W, P, DGC    |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| wood fiber - pillow                | 3   | throw        | pitchfork  | R, P, DGC, RT   |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| treated wood fiber - pillow        | 3   | throw        | pitchfork  | DGC, RT         |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| cross-linked polymer - particulate | 1   | blower       | skiploader | R, W, SS        |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| cross-linked polymer - pillow      | 2   | throw        | skiploader | R, DGC, RT      |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| sorbent clay - particulate         | 3   | blower       | skiploader | R, I, P         |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| polypropylene - particulate        | 3   | blower       | skiploader | W, SS, DGC      |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| expanded mineral - particulate     | 4   | blower       | skiploader | R, I, W, P, DGC |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |
| wood fiber - particulate           | 4   | blower       | skiploader | R, W, P, DGC    |            |             |                                    |   |        |        |          |                               |   |       |           |            |                            |   |        |        |         |                          |   |        |        |              |                     |   |       |           |               |                             |   |       |           |         |                                    |   |        |            |          |                               |   |       |            |            |                            |   |        |            |         |                             |   |        |            |            |                                |   |        |            |                 |                          |   |        |            |              |

Continued...

- ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> </ul> <p><b>Contains low boiling substance:</b><br/>Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none"> <li>▶ Check for bulging containers.</li> <li>▶ Vent periodically</li> <li>▶ Always release caps or seals slowly to ensure slow dissipation of vapours</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (&lt;=1 m/sec until fill pipe submerged to twice its diameter, then &lt;= 7 m/sec).</li> <li>▶ Avoid splash filling.</li> <li>▶ Do NOT use compressed air for filling discharging or handling operations.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Vapour may ignite on pumping or pouring due to static electricity.</li> <li>▶ <b>DO NOT use plastic buckets.</b></li> <li>▶ Earth and secure metal containers when dispensing or pouring product.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>  |

### Conditions for safe storage, including any incompatibilities

|                                |  |
|--------------------------------|--|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> <li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li> <li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>   |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

| Source                       | Ingredient  | Material name                | TWA                  | STEL                  | Peak          | Notes         |
|------------------------------|---|------------------------------|----------------------|-----------------------|---------------|---------------|
| Australia Exposure Standards | toluene   | Toluene                      | 191 mg/m3 / 50 ppm   | 574 mg/m3 / 150 ppm   | Not Available | Not Available |
| Australia Exposure Standards | propylene glycol monomethyl ether acetate, alpha-isomer | 1-Methoxy-2-propanol acetate | 274 mg/m3 / 50 ppm   | 548 mg/m3 / 100 ppm   | Not Available | Not Available |
| Australia Exposure Standards | acetone   | Acetone                      | 1185 mg/m3 / 500 ppm | 2375 mg/m3 / 1000 ppm | Not Available | Not Available |
| Australia Exposure Standards | n-butyl acetate   | n-Butyl acetate              | 713 mg/m3 / 150 ppm  | 950 mg/m3 / 200 ppm   | Not Available | Not Available |

## ColorSpec Acrylic Clear Coat 1 Litre

|                              |            |                  |                                |               |               |               |
|------------------------------|------------|------------------|--------------------------------|---------------|---------------|---------------|
| Australia Exposure Standards | isobutanol | Isobutyl alcohol | 152 mg/m <sup>3</sup> / 50 ppm | Not Available | Not Available | Not Available |
|------------------------------|------------|------------------|--------------------------------|---------------|---------------|---------------|

**EMERGENCY LIMITS**

| Ingredient  | Material name  | TEEL-1               | TEEL-2               | TEEL-3                |
|---|--|----------------------|----------------------|-----------------------|
| toluene   | Toluene  | Not Available        | Not Available        | Not Available         |
| propylene glycol monomethyl ether acetate, alpha-isomer | Propylene glycol monomethyl ether acetate, alpha-isomer; (1-Methoxypropyl-2-acetate) | Not Available        | Not Available        | Not Available         |
| propylene glycol monomethyl ether acetate, alpha-isomer | Propylene glycol monomethyl ether acetate, beta-isomer; (2-Methoxypropyl-1-acetate)  | Not Available        | Not Available        | Not Available         |
| xylene  | Xylenes  | Not Available        | Not Available        | Not Available         |
| acetone   | Acetone  | Not Available        | Not Available        | Not Available         |
| n-butyl acetate   | Butyl acetate, n-  | Not Available        | Not Available        | Not Available         |
| isobutanol  | Isobutyl alcohol   | 150 ppm              | 1,300 ppm            | 8000 ppm              |
| butyl benzyl phthalate                                  | Phthalic acid, benzyl butyl ester; (Benzyl butyl phthalate)                          | 15 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup> | 460 mg/m <sup>3</sup> |
| ethyl-3-ethoxypropionate                                | Propionic acid, 3-ethoxy-, ethyl ester; (Ethyl-3-ethoxypropionate)                   | 1.6 ppm              | 18 ppm               | 110 ppm               |

| Ingredient  | Original IDLH   | Revised IDLH  |
|---|-----------------|---------------|
| toluene   | 500 ppm         | Not Available |
| propylene glycol monomethyl ether acetate, alpha-isomer | Not Available   | Not Available |
| xylene  | 900 ppm         | Not Available |
| acetone   | 2,500 [LEL] ppm | Not Available |
| n-butyl acetate   | 1,700 [LEL] ppm | Not Available |
| isobutanol  | 1,600 ppm       | Not Available |
| butyl benzyl phthalate                                  | Not Available   | Not Available |
| naphtha petroleum, light aromatic solvent               | Not Available   | Not Available |
| ethyl-3-ethoxypropionate                                | Not Available   | Not Available |

**MATERIAL DATA**

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

Odour Safety Factor(OSF)

OSF=38 (ACETONE)

For n-butyl acetate

Odour Threshold Value: 0.0063 ppm (detection), 0.038-12 ppm (recognition)

Exposure at or below the recommended TLV-TWA is thought to prevent significant irritation of the eyes and respiratory passages as well as narcotic effects. In light of the lack of substantive evidence regarding teratogenicity and a review of acute oral data a STEL is considered inappropriate.

Odour Safety Factor(OSF)

OSF=3.8E2 (n-BUTYL ACETATE)

for propylene glycol monomethyl ether acetate (PGMEA)

Saturated vapour concentration: 4868 ppm at 20 C.

A two-week inhalation study found nasal effects to the nasal mucosa in animals at concentrations up to 3000 ppm. Differences in the teratogenic potential of the alpha (commercial grade) and beta isomers of PGMEA may be explained by the formation of different metabolites. The beta-isomer is thought to be oxidised to methoxypropionic acid, a homologue to methoxyacetic acid which is a known teratogen. The alpha- form is conjugated and excreted. PGMEA mixture (containing 2% to 5% beta isomer) is a mild skin and eye irritant, produces mild central nervous system effects in animals at 3000 ppm and produces mild CNS impairment and upper respiratory tract and eye irritation in humans at 1000 ppm. In rats exposed to 3000 ppm PGMEA produced slight foetotoxic effects (delayed sternbral ossification) - no effects on foetal development were seen in rabbits exposed at 3000 ppm.

For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.

High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans. Intentional toluene exposure (glue-sniffing) at maternally-intoxicating concentration has also produced birth defects. Foetotoxicity appears at levels associated with CNS narcosis and probably occurs only in those with chronic toluene-induced kidney failure. Exposure at or below the recommended TLV-TWA is thought to prevent transient headache and irritation, to provide a measure of safety for possible disturbances to human reproduction, the prevention of reductions in cognitive responses reported amongst humans inhaling greater than 40 ppm, and the significant risks of hepatotoxic, behavioural and nervous system effects (including impaired reaction time and incoordination). Although toluene/ethanol interactions are well recognised, the degree of protection afforded by the TLV-TWA among drinkers is not known.

Odour Safety Factor(OSF)

OSF=17 (TOLUENE)

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

Xylene vapour is an irritant to the eyes, mucous membranes and skin and causes narcosis at high concentrations. Exposure to doses sufficiently high to produce intoxication and unconsciousness also produces transient liver and kidney toxicity. Neurologic impairment is NOT evident amongst volunteers inhaling up to 400 ppm though complaints of ocular and upper respiratory tract irritation occur at 200 ppm for 3 to 5 minutes.

## ColorSpec Acrylic Clear Coat 1 Litre

Exposure to xylene at or below the recommended TLV-TWA and STEL is thought to minimise the risk of irritant effects and to produce neither significant narcosis or chronic injury. An earlier skin notation was deleted because percutaneous absorption is gradual and protracted and does not substantially contribute to the dose received by inhalation.

Odour Safety Factor(OSF)

OSF=4 (XYLENE)

For isobutanol:

Odour Threshold Value: 0.66-40 ppm (detection), 1.8-53 ppm (recognition) Although there do not appear to be reports of isobutyl alcohol causing auditory impairment or vestibular damage in humans (as with n-butanol) the recommended TLV-TWA recognises the slightly greater acute toxic potential of isobutanol versus n-butanol. Exposure at or below this limit is thought to significantly reduce the risk of skin irritation.

Odour Safety Factor (OSF)

OSF=31 (ISOBUTYL ALCOHOL)


NOTE M: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.005% w/w benzo[a]pyrene (EINECS No 200-028-5). This note applies only to certain complex oil-derived substances in Annex IV.

European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7). Note E shall also apply when the substance is classified as a carcinogen. This note applies only to certain complex oil-derived substances in Annex VI.

European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

### Exposure controls

| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 80%;">Type of Contaminant:</th> <th style="width: 20%;">Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td style="text-align: center;">0.25-0.5 m/s<br/>(50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td style="text-align: center;">0.5-1 m/s<br/>(100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td style="text-align: center;">1-2.5 m/s<br/>(200-500 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Lower end of the range</th> <th style="width: 50%;">Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s<br>(50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s<br>(200-500 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|---|---|----------------------|------------|--|---------------------------------|---|-------------------------------|--|-------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
|   | Type of Contaminant:  | Air Speed:           |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Personal protection</b>  |    |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Eye and face protection</b>  | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Skin protection</b>  | See Hand protection below   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Hands/feet protection</b>  | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>For esters:</p> <ul style="list-style-type: none"> <li>▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be</p>  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |



## ColorSpec Acrylic Clear Coat 1 Litre

|                         |   |
|-------------------------|---|
|                         | <p>checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>frequency and duration of contact,</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>Contaminated gloves should be replaced.</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>  | See Other protection below  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower. <ul style="list-style-type: none"> <li>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul> </li> </ul>   |
| <b>Thermal hazards</b>  | Not Available   |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

ColorSpec Acrylic Clear Coat 1 Litre

| Material          | CPI |
|-------------------|-----|
| BUTYL             | C   |
| BUTYL/NEOPRENE    | C   |
| CPE               | C   |
| HYPALON           | C   |
| NAT+NEOPR+NITRILE | C   |
| NATURAL RUBBER    | C   |
| NATURAL+NEOPRENE  | C   |
| NEOPRENE          | C   |
| NEOPRENE/NATURAL  | C   |
| NITRILE           | C   |
| NITRILE+PVC       | C   |
| PE                | C   |
| PE/EVAL/PE        | C   |
| PVA               | C   |
| PVC               | C   |
| PVDC/PE/PVDC      | C   |
| SARANEX-23        | C   |
| SARANEX-23-2-PLY  | C   |
| TEFLON            | C   |
| VITON             | C   |

## Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator   |
|------------------------------------|----------------------|----------------------|--------------------------|
| up to 5 x ES                       | AX-AUS / Class 1 P2  | -                    | AX-PAPR-AUS / Class 1 P2 |
| up to 25 x ES                      | Air-line*            | AX-2 P2              | AX-PAPR-2 P2             |
| up to 50 x ES                      | -                    | AX-3 P2              | -                        |
| 50+ x ES                           | -                    | Air-line**           | -                        |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

## ColorSpec Acrylic Clear Coat 1 Litre

|                   |   |
|-------------------|---|
| VITON/BUTYL       | C |
| VITON/CHLOROBUTYL | C |
| VITON/NEOPRENE    | C |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|   |  |  |                |
|---|--|--|----------------|
| <b>Appearance</b>                                   | Clear viscous highly flammable liquid with a strong solvent odour. |  |                |
| <b>Physical state</b>                               | Liquid   | <b>Relative density (Water = 1)</b>            | 0.90-1.00      |
| <b>Odour</b>  | Not Available  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available  | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Applicable   | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | 56-145   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | -18 (OC)   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | HIGHLY FLAMMABLE.  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | 12.8   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | 1  | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | 24.7 @20C  | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Not Available  | <b>pH as a solution (1%)</b>                   | Not Applicable |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                  |  |
|------------------|--|
| <b>Inhaled</b>   | <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination</p> <p>Inhalation hazard is increased at higher temperatures.</p> |
| <b>Ingestion</b> | <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>In a 14-day study of butyl benzyl phthalate in rats, exposure to 25000 ppm or more resulted in lower body weight gains. Thymic atrophy occurred in all 100000 ppm rats and testicular degeneration was observed in all 50000 and 100000 ppm males. No compound related effects were seen in a companion study in mice receiving 25000 ppm in feed. In a similar 13-week study, lower body weight gains and testicular degeneration, characterised by loss of germinal epithelium of the seminiferous tubules were seen in male rats receiving 25000 ppm whereas compound related effects in mice were limited to lower body weight gains in male mice exposed to concentrations of 1600 ppm or more and in 12500 ppm females. The testicular degeneration in rats may</p>  |

ColorSpec Acrylic Clear Coat 1 Litre

|                     |   |
|---------------------|---|
|                     | <p>be related to the conversion of the phthalate to monobutylphthalate which has been shown to produce testicular atrophy. Rats exposed to 2000 to 4000 mg in feed for 2-weeks showed dose-related posterior body stiffness and incoordination of the hind limbs which was more severe in males. These signs generally disappeared by the end of a 1-week recovery period. In a follow-up 6-week neurological study, body weight gains of rats exposed to 1500 or 3000 mg butyl benzyl phthalate/kg body weight were lower than those of the controls, and transient hind limb stiffness was observed in the 3000 mg/kg group, mainly in males.</p> <p>Histopathology of tissues from the central and peripheral nervous system</p> <p>no-observed-effect-level (NOEL) in a 90 day study with rats administered feed containing up to 2% of the phthalate, by weight, was 0.5%. After 14-weeks of a 2-year study with rats exposed to 6000 or 12000 ppm butyl benzyl phthalate in feed, compound related mortality in males resulted from unexplained internal haemorrhaging.</p> <p>It has been postulated that intraperitoneal injection produces acute depression of the central nervous system.</p> <p>Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis</p>   |
| <b>Skin Contact</b> | <p>The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either</p> <ul style="list-style-type: none"> <li>▶ produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or</li> <li>▶ produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.</li> </ul> <p>Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p>   |
| <b>Eye</b>          | <p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.</p>   |
| <b>Chronic</b>      | <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p> <p>Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.</p> <p>There is sufficient evidence to provide a strong presumption that human exposure to the material may result in developmental toxicity, generally on the basis of:</p> <ul style="list-style-type: none"> <li>- clear results in appropriate animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.</li> </ul> <p>Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.</p> <p>On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> |

|  |  |                                    |
|--|--|------------------------------------|
| <b>ColorSpec Acrylic Clear Coat 1 Litre</b>                    | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | Not Available  | Not Available                      |
| <b>toluene</b>   | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | Dermal (rabbit) LD50: 12124 mg/kg <sup>[2]</sup>           | Eye (rabbit): 2mg/24h - SEVERE     |
|  | Inhalation (rat) LC50: 49 mg/l/4h <sup>[2]</sup>           | Eye (rabbit):0.87 mg - mild        |
|  | Oral (rat) LD50: 636 mg/kg <sup>[2]</sup>                  | Eye (rabbit):100 mg/30sec - mild   |
|  |  | Skin (rabbit):20 mg/24h-moderate   |
|  |  | Skin (rabbit):500 mg - moderate    |
| <b>propylene glycol monomethyl ether acetate, alpha-isomer</b> | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>              | Not Available                      |
|  | Inhalation (rat) LC50: 6510.0635325 mg/l/6h <sup>[2]</sup> |                                    |
|  | Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>                |                                    |
| <b>xylene</b>  | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>           | Eye (human): 200 ppm irritant      |
|  | Inhalation (rat) LC50: 4994.295 mg/l/4h <sup>[2]</sup>     | Eye (rabbit): 5 mg/24h SEVERE      |
|  | Oral (rat) LD50: 4300 mg/kg <sup>[2]</sup>                 | Eye (rabbit): 87 mg mild           |
|  |  | Skin (rabbit):500 mg/24h moderate  |
| <b>acetone</b>   | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | Dermal (rabbit) LD50: 20000 mg/kg <sup>[2]</sup>           | Eye (human): 500 ppm - irritant    |
|  | Inhalation (rat) LC50: 100.2 mg/l/8hr <sup>[2]</sup>       | Eye (rabbit): 20mg/24hr - moderate |
|  | Oral (rat) LD50: 5800 mg/kg <sup>[2]</sup>                 | Eye (rabbit): 3.95 mg - SEVERE     |
|  |  | Skin (rabbit): 500 mg/24hr - mild  |
|  |  | Skin (rabbit):395mg (open) - mild  |
| <b>n-butyl acetate</b>   | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|  | Dermal (rabbit) LD50: 3200 mg/kg <sup>[2]</sup>            | Eye ( human): 300 mg               |

## ColorSpec Acrylic Clear Coat 1 Litre

|   |   |  |
|---|---|--|
|   | Inhalation (rat) LC50: 1.802 mg/l4 h <sup>[1]</sup>       | Eye (rabbit): 20 mg (open)-SEVERE  |
|   | Oral (rat) LD50: 10768 mg/kg <sup>[2]</sup>               | Eye (rabbit): 20 mg/24h - moderate<br>Skin (rabbit): 500 mg/24h-moderate |
| isobutanol                                | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|   | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>          | Eye (rabbit): 2 20 mg/24h-moderate                                       |
|   | Inhalation (rat) LC50: 19.2 mg/l/4h <sup>[2]</sup>        | Eye (rabbit): 2 mg/24h - SEVERE  |
|   | Oral (rat) LD50: 2460 mg/kg <sup>[2]</sup>                | Skin (rabbit): mg (open)-SEVERE  |
| butyl benzyl phthalate                    | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|   | dermal (rat) LD50: 6700 mg/kg <sup>[2]</sup>              | Not Available  |
|   | Oral (rat) LD50: 2330 mg/kg <sup>[2]</sup>                |  |
| naphtha petroleum, light aromatic solvent | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|   | Dermal (rabbit) LD50: >1900 mg/kg <sup>[1]</sup>          | Not Available  |
|   | Inhalation (rat) LC50: >7331.62506 mg/l/8h <sup>[2]</sup> |  |
|   | Oral (rat) LD50: >4500 mg/kg <sup>[1]</sup>               |  |
| ethyl-3-ethoxypropionate                  | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|   | Dermal (rabbit) LD50: 4076 mg/kg <sup>[2]</sup>           | Eye (rabbit): 500mg/24h - mild   |
|   | Inhalation (rat) LC50: 1248.57375 mg/l/4h <sup>[2]</sup>  | Skin (rabbit):10 mg/24h open mild  |
|   | Oral (rat) LD50: >3200 mg/kg <sup>[1]</sup>               |  |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |  |
|---|--|
| TOLUENE   | For toluene:   |
|   | <b>Acute Toxicity</b>  |
|   | Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death. Similar effects are observed in short-term animal studies.  |
|   | <b>Humans</b> - Toluene ingestion or inhalation can result in severe central nervous system depression, and in large doses, can act as a narcotic. The ingestion of about 60 mL resulted in fatal nervous system depression within 30 minutes in one reported case.  |
|   | Constriction and necrosis of myocardial fibers, markedly swollen liver, congestion and haemorrhage of the lungs and acute tubular necrosis were found on autopsy.  |
|   | Central nervous system effects (headaches, dizziness, intoxication) and eye irritation occurred following inhalation exposure to 100 ppm toluene 6 hours/day for 4 days.   |
|   | Exposure to 600 ppm for 8 hours resulted in the same and more serious symptoms including euphoria, dilated pupils, convulsions, and nausea. Exposure to 10,000-30,000 ppm has been reported to cause narcosis and death  |
|   | Toluene can also strip the skin of lipids causing dermatitis   |
|   | <b>Animals</b> - The initial effects are instability and incoordination, lachrymation and sniffles (respiratory exposure), followed by narcosis. Animals die of respiratory failure from severe nervous system depression. Cloudy swelling of the kidneys was reported in rats following inhalation exposure to 1600 ppm, 18-20 hours/day for 3 days |
|   | <b>Subchronic/Chronic Effects:</b>   |
| Repeat doses of toluene cause adverse central nervous system effects and can damage the upper respiratory system, the liver, and the kidney. Adverse effects occur as a result from both oral and the inhalation exposures. A reported lowest-observed-effect level in humans for adverse neurobehavioral effects is 88 ppm.  |  |
| <b>Humans</b> - Chronic occupational exposure and incidences of toluene abuse have resulted in hepatomegaly and liver function changes. It has also resulted in nephrotoxicity and, in one case, was a cardiac sensitiser and fatal cardiotoxin.  |  |
| Neural and cerebellar dystrophy were reported in several cases of habitual "glue sniffing." An epidemiological study in France on workers chronically exposed to toluene fumes reported leukopenia and neutropenia. Exposure levels were not given in the secondary reference; however, the average urinary excretion of hippuric acid, a metabolite of toluene, was given as 4 g/L compared to a normal level of 0.6 g/L   |  |
| <b>Animals</b> - The major target organs for the subchronic/chronic toxicity of toluene are the nervous system, liver, and kidney. Depressed immune response has been reported in male mice given doses of 105 mg/kg/day for 28 days. Toluene in corn oil administered to F344 male and female rats by gavage 5 days/week for 13 weeks, induced prostration, hypoactivity, ataxia, piloerection, lachrymation, excess salivation, and body tremors at doses 2500 mg/kg. Liver, kidney, and heart weights were also increased at this dose and histopathologic lesions were seen in the liver, kidneys, brain and urinary bladder. The no-observed-adverse effect level (NOAEL) for the study was 312 mg/kg (223 mg/kg/day) and the lowest-observed-adverse effect level (LOAEL) for the study was 625 mg/kg (446 mg/kg/day).  |  |
| <b>Developmental/Reproductive Toxicity</b>  |  |
| Exposures to high levels of toluene can result in adverse effects in the developing human foetus. Several studies have indicated that high levels of toluene can also adversely effect the developing offspring in laboratory animals.  |  |
| <b>Humans</b> - Variable growth, microcephaly, CNS dysfunction, attentional deficits, minor craniofacial and limb abnormalities, and developmental delay were seen in three children exposed to toluene in utero as a result of maternal solvent abuse before and during pregnancy  |  |
| <b>Animals</b> - Sternebral alterations, extra ribs, and missing tails were reported following treatment of rats with 1500 mg/m <sup>3</sup> toluene 24 hours/day during days 9-14 of gestation. Two of the dams died during the exposure. Another group of rats received 1000 mg/m <sup>3</sup> 8 hours/day during days 1-21 of gestation. No maternal deaths or toxicity occurred, however, minor skeletal retardation was present in the exposed fetuses. CFLP Mice were exposed to 500 or 1500 mg/m <sup>3</sup> toluene continuously during days 6-13 of pregnancy. All dams died at the high dose during the first 24 hours of exposure, however none died at 500 mg/m <sup>3</sup> . Decreased foetal weight was reported, but there were no differences in the incidences of skeletal malformations or anomalies between the treated and control offspring. |  |
| <b>Absorption</b> - Studies in humans and animals have demonstrated that toluene is readily absorbed via the lungs and the gastrointestinal tract. Absorption through the skin is estimated at about 1% of that absorbed by the lungs when exposed to toluene vapor.  |  |
| Dermal absorption is expected to be higher upon exposure to the liquid; however, exposure is limited by the rapid evaporation of toluene.   |  |
| <b>Distribution</b> - In studies with mice exposed to radiolabeled toluene by inhalation, high levels of radioactivity were present in body fat, bone marrow, spinal nerves, spinal cord, and brain white matter. Lower levels of radioactivity were present in blood, kidney, and liver. Accumulation of toluene has generally been found in adipose tissue, other tissues with high fat content, and in highly vascularised tissues.  |  |

## ColorSpec Acrylic Clear Coat 1 Litre

|   |   |
|---|---|
|   | <p><b>Metabolism</b> - The metabolites of inhaled or ingested toluene include benzyl alcohol resulting from the hydroxylation of the methyl group. Further oxidation results in the formation of benzaldehyde and benzoic acid. The latter is conjugated with glycine to yield hippuric acid or reacted with glucuronic acid to form benzoyl glucuronide. <i>o</i>-cresol and <i>p</i>-cresol formed by ring hydroxylation are considered minor metabolites</p> <p><b>Excretion</b> - Toluene is primarily (60-70%) excreted through the urine as hippuric acid. The excretion of benzoyl glucuronide accounts for 10-20%, and excretion of unchanged toluene through the lungs also accounts for 10-20%. Excretion of hippuric acid is usually complete within 24 hours after exposure.</p>  |
| <p><b>PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER</b></p> | <p>for propylene glycol ethers (PGEs):</p> <p>Typical propylene glycol ethers include propylene glycol <i>n</i>-butyl ether (PnB); dipropylene glycol <i>n</i>-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).</p> <p>Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on reproductive organs, the developing embryo and fetus, blood (haemolytic effects), or thymus, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids.</p> <p>Longer chain length homologues in the ethylene series are not associated with the reproductive toxicity but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid. The predominant alpha isomer of all the PGEs (thermodynamically favored during manufacture of PGEs) is a secondary alcohol incapable of forming an alkoxypropionic acid. In contrast beta-isomers are able to form the alkoxypropionic acids and these are linked to teratogenic effects (and possibly haemolytic effects).</p> <p>This alpha isomer comprises greater than 95% of the isomeric mixture in the commercial product.</p> <p>Because the alpha isomer cannot form an alkoxypropionic acid, this is the most likely reason for the lack of toxicity shown by the PGEs as distinct from the lower molecular weight ethylene glycol ethers. More importantly, however, very extensive empirical test data show that this class of commercial-grade glycol ether presents a low toxicity hazard. PGEs, whether mono, di- or tripropylene glycol-based (and no matter what the alcohol group), show a very similar pattern of low to non-detectable toxicity of any type at doses or exposure levels greatly exceeding those showing pronounced effects from the ethylene series. One of the primary metabolites of the propylene glycol ethers is propylene glycol, which is of low toxicity and completely metabolised in the body.</p> <p>As a class, the propylene glycol ethers are rapidly absorbed and distributed throughout the body when introduced by inhalation or oral exposure. Dermal absorption is somewhat slower but subsequent distribution is rapid. Most excretion for PGEs is via the urine and expired air. A small portion is excreted in the faeces.</p> <p>As a group PGEs exhibits low acute toxicity by the oral, dermal, and inhalation routes. Rat oral LD50s range from &gt;3,000 mg/kg (PnB) to &gt;5,000 mg/kg (DPMA). Dermal LD50s are all &gt; 2,000 mg/kg (PnB, &amp; DPnB; where no deaths occurred), and ranging up to &gt;15,000 mg/kg (TPM). Inhalation LC50 values were higher than 5,000 mg/m3 for DPMA (4-hour exposure), and TPM (1-hour exposure). For DPnB the 4-hour LC50 is &gt;2,040 mg/m3. For PnB, the 4-hour LC50 was &gt;651 ppm (&gt;3,412 mg/m3), representing the highest practically attainable vapor level. No deaths occurred at these concentrations. PnB and TPM are moderately irritating to eyes while the remaining category members are only slightly irritating to nonirritating. PnB is moderately irritating to skin while the remaining category members are slightly to non-irritating.</p> <p>None are skin sensitizers.</p> <p>In repeated dose studies ranging in duration from 2 to 13 weeks, few adverse effects were found even at high exposure levels and effects that did occur were mild in nature. By the oral route of administration, NOAELs of 350 mg/kg-d (PnB – 13 wk) and 450 mg/kg-d (DPnB – 13 wk) were observed for liver and kidney weight increases (without accompanying histopathology). LOAELs for these two chemicals were 1000 mg/kg-d (highest dose tested). Dermal repeated-dose toxicity tests have been performed for many PGEs. For PnB, no effects were seen in a 13-wk study at doses as high as 1,000 mg/kg-d. A dose of 273 mg/kg-d constituted a LOAEL (increased organ weights without histopathology) in a 13-week dermal study for DPnB. For TPM, increased kidney weights (no histopathology) and transiently decreased body weights were found at a dose of 2,895 mg/kg-d in a 90-day study in rabbits. By inhalation, no effects were observed in 2-week studies in rats at the highest tested concentrations of 3244 mg/m3 (600 ppm) for PnB and 2,010 mg/m3 (260 ppm) for DPnB. TPM caused increased liver weights without histopathology by inhalation in a 2-week study at a LOAEL of 360 mg/m3 (43 ppm). In this study, the highest tested TPM concentration, 1010 mg/m3 (120 ppm), also caused increased liver weights without accompanying histopathology. Although no repeated-dose studies are available for the oral route for TPM, or for any route for DPMA, it is anticipated that these chemicals would behave similarly to other category members.</p> <p>One and two-generation reproductive toxicity testing has been conducted in mice, rats, and rabbits via the oral or inhalation routes of exposure on PM and PMA. In an inhalation rat study using PM, the NOAEL for parental toxicity is 300 ppm (1106 mg/m3) with decreases in body and organ weights occurring at the LOAEL of 1000 ppm (3686 mg/m3). For offspring toxicity the NOAEL is 1000 ppm (3686 mg/m3), with decreased body weights occurring at 3000 ppm (11058 mg/m3). For PMA, the NOAEL for parental and offspring toxicity is 1000 mg/kg/d. in a two generation gavage study in rats. No adverse effects were found on reproductive organs, fertility rates, or other indices commonly monitored in such studies. In addition, there is no evidence from histopathological data from repeated-dose studies for the category members that would indicate that these chemicals would pose a reproductive hazard to human health.</p> <p>In developmental toxicity studies many PGEs have been tested by various routes of exposure and in various species at significant exposure levels and show no frank developmental effects. Due to the rapid hydrolysis of DPMA to DPM, DPMA would not be expected to show teratogenic effects. At high doses where maternal toxicity occurs (e.g., significant body weight loss), an increased incidence of some anomalies such as delayed skeletal ossification or increased 13th ribs, have been reported. Commercially available PGEs showed no teratogenicity.</p> <p>The weight of the evidence indicates that propylene glycol ethers are not likely to be genotoxic. <i>In vitro</i>, negative results have been seen in a number of assays for PnB, DPnB, DPMA and TPM. Positive results were only seen in 3 out of 5 chromosome aberration assays in mammalian cells with DPnB. However, negative results were seen in a mouse micronucleus assay with DPnB and PM. Thus, there is no evidence to suggest these PGEs would be genotoxic <i>in vivo</i>. In a 2-year bioassay on PM, there were no statistically significant increases in tumors in rats and mice.</p> <p>A BASF report (in ECETOC ) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects.</p> <p>The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer. Hazard appears low but emphasizes the need for care in handling this chemical. [I.C.I]</p> <p>A BASF report (in ECETOC ) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects. The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer. Hazard appears low but emphasizes the need for care in handling this chemical. [I.C.I] *Shin-Etsu SDS</p> |
| <p><b>XYLENE</b></p>  | <p>Reproductive effector in rats</p>  |
| <p><b>ACETONE</b></p>   | <p>for acetone:</p> <p>The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage. Acetone-induced increases in relative kidney weight changes were observed in male and female rats used in the oral 13-week study. Acetone treatment caused increases in the relative liver weight in male and female rats that were not associated with histopathologic effects and the effects may have been associated with microsomal enzyme induction. Haematologic effects consistent with macrocytic anaemia were also noted in male rats along with hyperpigmentation in the spleen. The most notable findings in the mice were increased liver and decreased spleen weights. Overall, the no-observed-effect-levels in the drinking water study were 1% for male rats (900 mg/kg/d) and male mice (2258 mg/kg/d), 2% for female mice (5945 mg/kg/d), and 5% for female rats (3100 mg/kg/d). For developmental effects, a statistically significant reduction in foetal weight, and a slight, but statistically significant increase in the percent incidence of later resorptions were seen in mice at 15,665 mg/m3 and in rats at 26,100 mg/m3. The no-observable-effect level for developmental toxicity was determined to be 5220 mg/m3 for both rats and mice.</p> <p>Teratogenic effects were not observed in rats and mice tested at 26,110 and 15,665 mg/m3, respectively. Lifetime dermal carcinogenicity studies in mice treated with up to 0.2 mL of acetone did not reveal any increase in organ tumor incidence relative to untreated control animals.</p> <p>The scientific literature contains many different studies that have measured either the neurobehavioural performance or neurophysiological response of humans exposed to acetone. Effect levels ranging from about 600 to greater than 2375 mg/m3 have been reported. Neurobehavioral studies with acetone-exposed employees have recently shown that 8-hr exposures in excess of 2375 mg/m3 were not associated with any dose-related changes in response time, vigilance, or digit span scores. Clinical case studies, controlled human volunteer studies, animal research, and occupational field evaluations all indicate</p>  |

## ColorSpec Acrylic Clear Coat 1 Litre

|  |   |
|--|---|
|  | that the NOAEL for this effect is 2375 mg/m3 or greater.  |
| ISOBUTANOL                                   | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p>   |
| BUTYL BENZYL PHTHALATE                       | <p>The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited, cytoplasmic organelles that are found in the cells of animals, plants, fungi and protozoa. Peroxisome proliferators include certain hypolipidaemic drugs, phthalate ester plasticisers, industrial solvents, herbicides, food flavours, leukotriene D4 antagonists and hormones. Numerous studies in rats and mice have demonstrated the hepatocarcinogenic effects of peroxisome proliferators, and these compounds have been unequivocally established as carcinogens. However it is generally conceded that compounds inducing proliferation in rats and mice have little, if any, effect on human liver except at very high doses or extreme conditions of exposure.</p> <p>for benzyl butyl phthalate:</p> <p><b>Repeat dose toxicity:</b> The repeated-dose toxicity of BBP has been well investigated in studies, primarily in the rat, in which dose-response was well characterised. Effects observed consistently have been decreases in body weight gain (often accompanied by decreases in food consumption) and increases in organ to body weight ratios, particularly for the kidney and liver. Histopathological effects on the pancreas and kidney and haematological effects have also been observed. At higher doses, degenerative effects on the testes and, occasionally, histopathological effects on the liver have been reported. In specialised investigations, peroxisomal proliferation in the liver has been observed, although potency in this regard was less than that for other phthalates, such as bis(2-ethylhexyl) phthalate (DEHP).</p> <p><b>Reproductive Toxicity and Teratology Studies</b></p> <p>Groups of male F344/N rats given 20, 200, or 2200 mg/kg body weight butyl benzyl phthalate daily in feed for 10 weeks resulted in significantly decreased prostate gland, right cauda, right epididymis, and right testis weights at the highest dose versus those of the controls (NTP, 1997). Additionally, the epididymal spermatozoal concentrations in males given the 200 and 2200 mg/kg levels were significantly less than the controls. Females mated to 20 and 200 mg/kg males exhibited maternal body weights similar to those of females mated to control males. Litter data between the two dose groups and controls were also similar. Females mated to 2200 mg/kg males were initially found to be sperm positive; however, at necropsy, none of the females were pregnant. The fertility indices of the males and females were observed to be significantly lower than those of the controls.</p> <p><b>Developmental Toxicity:</b> In several well-conducted studies in rats and mice, BBP has induced marked developmental effects, but only at dose levels that induce significant maternal toxicity.</p> <p><b>Carcinogenicity Studies</b></p> <p>In a 2-year study, groups of male F344/N rats were given 120, 240, or 500 mg/kg body weight butyl benzyl phthalate daily in feed and females were given 300, 600, or 1200 mg/kg/day (NTP, 1997). At the highest dose, the incidences of pancreatic acinar cell adenoma and adenoma or carcinoma (combined) were significantly greater in males than those in the controls. In females, the incidence of transitional epithelial hyperplasia was significantly greater than that in the controls. Specifically, two transitional epithelial papillomas in the urinary bladder were seen.</p> <p>It was concluded that there was "some evidence" of carcinogenicity in male rats, based on an increased incidence of pancreatic tumours, and equivocal evidence in female rats, based on marginal increases in pancreatic and bladder tumours. Dietary restriction prevented full expression of the pancreatic tumours and delayed appearance of the bladder tumours. There was no evidence of carcinogenicity in mice.</p> <p><b>Genotoxicity Studies</b></p> <p>At concentrations up to 11,550 ug/plate butyl benzyl phthalate in <i>Salmonella typhimurium</i> strains TA98, TA100, TA1535, and TA1537, no mutagenic response was obtained, in the presence or absence of metabolic activation (S9) (NTP, 1997). <i>In vitro</i> studies with L5178Y mouse lymphoma cells and cultured Chinese hamster ovary cells, both conducted with and without S9, were also negative. In germ cells of male <i>Drosophila melanogaster</i>, no induction of sex-linked recessive lethal mutations was observed. In contrast to these results, butyl benzyl phthalate gave positive responses in two <i>in vivo</i> mouse studies. In one experiment, sister chromatid exchanges were weakly positive at 23 and 42 hours. In the other study, chromosomal aberrations were induced in bone marrow cells 17 hours after intraperitoneal injection of 5000 mg/kg of the compound.</p> <p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).</p> <p>Reproductive effector in rats.</p>   |
| NAPHTHA PETROLEUM,<br>LIGHT AROMATIC SOLVENT | <p>For trimethylbenzenes:</p> <p>Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Occupationally, inhalation and dermal exposures are the most important routes of absorption although systemic intoxication from dermal absorption is not likely to occur due to the dermal irritation caused by the chemical prompting quick removal. Following oral administration of the chemical to rats, 62.6% of the dose was recovered as urinary metabolites indicating substantial absorption. 1,2,4-Trimethylbenzene is lipophilic and may accumulate in fat and fatty tissues. In the blood stream, approximately 85% of the chemical is bound to red blood cells. Metabolism occurs by side-chain oxidation to form alcohols and carboxylic acids which are then conjugated with glucuronic acid, glycine, or sulfates for urinary excretion. After a single oral dose to rats of 1200 mg/kg, urinary metabolites consisted of approximately 43.2% glycine, 6.6% glucuronic, and 12.9% sulfuric acid conjugates. The two principle metabolites excreted by rabbits after oral administration of 438 mg/kg/day for 5 days were 2,4-dimethylbenzoic acid and 3,4-dimethylhippuric acid. The major routes of excretion of 1,2,4-trimethylbenzene are exhalation of parent compound and elimination of urinary metabolites. Half-times for urinary metabolites were reported as 9.5 hours for glycine, 22.9 hours for glucuronide, and 37.6 hours for sulfuric acid conjugates.</p> <p><b>Acute Toxicity</b> Direct contact with liquid 1,2,4-trimethylbenzene is irritating to the skin and breathing the vapor is irritating to the respiratory tract causing pneumonitis. Breathing high concentrations of the chemical vapor causes headache, fatigue, and drowsiness. In humans liquid 1,2,4-trimethylbenzene is irritating to the skin and inhalation of vapor causes chemical pneumonitis. High concentrations of vapor (5000-9000 ppm) cause headache, fatigue, and drowsiness. The concentration of 5000 ppm is roughly equivalent to a total of 221 mg/kg assuming a 30 minute exposure period (see end note 1).</p> <p>Animals - Mice exposed to 8130-9140 ppm 1,2,4-trimethylbenzene (no duration given) had loss of righting response and loss of reflexes. Direct dermal contact with the chemical (no species given) causes vasodilation, erythema, and irritation (U.S. EPA). Seven of 10 rats died after an oral dose of 2.5 mL of a mixture of trimethylbenzenes in olive oil (average dose approximately 4.4 g/kg). Rats and mice were exposed by inhalation to a coal tar distillate containing about 70% 1,3,5- and 1,2,4-trimethylbenzene; no pathological changes were noted in either species after exposure to 1800-2000 ppm for up to 48 continuous hours, or in rats after 14 exposures of 8 hours each at the same exposure levels. No effects were reported for rats exposed to a mixture of trimethylbenzenes at 1700 ppm for 10 to 21 days.</p> <p><b>Neurotoxicity</b> 1,2,4-Trimethylbenzene depresses the central nervous system. Exposure to solvent mixtures containing the chemical causes headache, fatigue, nervousness, and drowsiness. Occupationally, workers exposed to a solvent containing 50% 1,2,4-trimethylbenzene had nervousness, headaches, drowsiness, and vertigo (U.S. EPA). Headache, fatigue, and drowsiness were reported for workers exposed (no dose given) to paint thinner containing 80% 1,2,4- and 1,3,5-trimethylbenzenes.</p> <p>Results of the developmental toxicity study indicate that the C9 fraction caused adverse neurological effects at the highest dose (1500 ppm) tested.</p> <p><b>Subchronic/Chronic Toxicity</b> Long-term exposure to solvents containing 1,2,4-trimethylbenzene may cause nervousness, tension, and bronchitis. Painters that worked for several years with a solvent containing 50% 1,2,4- and 30% 1,3,5-trimethylbenzene showed nervousness, tension and anxiety, asthmatic bronchitis, anemia, and alterations in blood clotting; haematological effects may have been due to trace amounts of benzene.</p> <p>Rats given 1,2,4-trimethylbenzene orally at doses of 0.5 or 2.0 g/kg/day, 5 days/week for 4 weeks. All rats exposed to the high dose died and 1 rat in the low dose died (no times given); no other effects were reported. Rats exposed by inhalation to 1700 ppm of a trimethylbenzene isomeric mixture for 4 months had decreased weight gain, lymphopenia and neutrophilia.</p> <p><b>Genotoxicity:</b> Results of mutagenicity testing, indicate that the C9 fraction does not induce gene mutations in prokaryotes (<i>Salmonella typhimurium</i>/mammalian microsome assay); or in mammalian cells in culture (in Chinese hamster ovary cells with and without activation). The C9 fraction does not induce chromosome mutations in Chinese hamster ovary cells with and without activation; does not induce chromosome aberrations in the bone marrow of Sprague-Dawley rats exposed by inhalation (6 hours/day for 5 days); and does not induce sister chromatid exchange in Chinese hamster ovary cells with and without activation.</p> |

## ColorSpec Acrylic Clear Coat 1 Litre

**Developmental/Reproductive Toxicity:** A three-generation reproductive study on the C9 fraction was conducted. CD rats (30/sex/group) were exposed by inhalation to the C9 fraction at concentrations of 0, 100, 500, or 1500 ppm (0, 100, 500, or 1500 mg/kg/day) for 6 hours/day, 5 days/week. There was evidence of parental and reproductive toxicity at all dose levels. Indicators of parental toxicity included reduced body weights, increased salivation, hunched posture, aggressive behavior, and death. Indicators of adverse reproductive system effects included reduced litter size and reduced pup body weight. The LOEL was 100 ppm; a no-observed-effect level was not established. Developmental toxicity, including possible developmental neurotoxicity, was evident in rats in a 3-generation reproductive study.

No effects on fecundity or fertility occurred in rats treated dermally with up to 0.3 mL/rat/day of a mixture of trimethylbenzenes, 4-6 hours/day, 5 days/week over one generation.

For C9 aromatics (typically trimethylbenzenes - TMBs)

#### Acute Toxicity

Acute toxicity studies (oral, dermal and inhalation routes of exposure) have been conducted in rats using various solvent products containing predominantly mixed C9 aromatic hydrocarbons (CAS RN 64742-95-6). Inhalation LC50's range from 6,000 to 10,000 mg/m<sup>3</sup> for C9 aromatic naphtha and 18,000 to 24,000 mg/m<sup>3</sup> for 1,2,4 and 1,3,5-TMB, respectively. A rat oral LD50 reported for 1,2,4-TMB is 5 grams/kg bw and a rat dermal LD50 for the C9 aromatic naphtha is >4 mL/kg bw. These data indicate that C9 aromatic solvents show that LD50/LC50 values are greater than limit doses for acute toxicity studies established under OECD test guidelines.

#### Irritation and Sensitization

Several irritation studies, including skin, eye, and lung/respiratory system, have been conducted on members of the category. The results indicate that C9 aromatic hydrocarbon solvents are mildly to moderately irritating to the skin, minimally irritating to the eye, and have the potential to irritate the respiratory tract and cause depression of respiratory rates in mice. Respiratory irritation is a key endpoint in the current occupational exposure limits established for C9 aromatic hydrocarbon solvents and trimethylbenzenes. No evidence of skin sensitization was identified.

#### Repeated Dose Toxicity

**Inhalation:** The results from a subchronic (3 month) neurotoxicity study and a one-year chronic study (6 hr/day, 5 days/week) indicate that effects from inhalation exposure to C9 Aromatic Hydrocarbon Solvents on systemic toxicity are slight. A battery of neurotoxicity and neurobehavioral endpoints were evaluated in the 3-month inhalation study on C9 aromatic naphtha tested at concentrations of 0, 101, 452, or 1320 ppm (0, 500, 2,220, or 6,500 mg/m<sup>3</sup>). In this study, other than a transient weight reduction in the high exposure group (not statistically significant at termination of exposures), no effects were reported on neuropathology or neuro/behavioral parameters. The NOAEL for systemic and/or neurotoxicity was 6,500 mg/m<sup>3</sup>, the highest concentration tested. In an inhalation study of a commercial blend, rats were exposed to C9 aromatic naphtha concentrations of 0, 96, 198, or 373 ppm (0, 470, 970, 1830 mg/m<sup>3</sup>) for 6 hr/day, 5 days/week, for 12 months. Liver and kidney weights were increased in the high exposure group but no accompanying histopathology was observed in these organs.

The NOAEL was considered to be the high exposure level of 373 ppm, or 1830 mg/m<sup>3</sup>. In two subchronic rat inhalation studies, both of three months duration, rats were exposed to the individual TMB isomers (1,2,4-and 1,3,5-) to nominal concentrations of 0, 25, 100, or 250 ppm (0, 123, 492, or 1230 mg/m<sup>3</sup>). Respiratory irritation was observed at 492 (100 ppm) and 1230 mg/m<sup>3</sup> (250 ppm) and no systemic toxicity was observed in either study. For both pure isomers, the NOELs are 25 ppm or 123 mg/m<sup>3</sup> for respiratory irritation and 250 ppm or 1230 mg/m<sup>3</sup> for systemic effects.

**Oral:** The C9 aromatic naphtha has not been tested via the oral route of exposure. Individual TMB isomers have been evaluated in a series of repeated-dose oral studies ranging from 14 days to 3 months over a wide range of doses. The effects observed in these studies included increased liver and kidney weights, changes in blood chemistry, increased salivation, and decreased weight gain at higher doses. Organ weight changes appeared to be adaptive as they were not accompanied by histopathological effects. Blood changes appeared sporadic and without pattern. One study reported hyaline droplet nephropathy in male rats at the highest dose (1000 mg/kg bw-day), an effect that is often associated with alpha-2mu-globulin-induced nephropathy and not considered relevant to humans. The doses at which effects were detected were 100 mg/kg-bw day or above (an exception was the pilot 14 day oral study - LOAEL 150 mg/kg bw-day - but the follow up three month study had a LOAEL of 600 mg/kg/bw-day with a NOAEL of 200 mg/kg bw-day). Since effects generally were not severe and could be considered adaptive or spurious, oral exposure does not appear to pose a high toxicity hazard for pure trimethylbenzene isomers.

#### Mutagenicity

In vitro genotoxicity testing of a variety of C9 aromatics has been conducted in both bacterial and mammalian cells. In vitro point mutation tests were conducted with *Salmonella typhimurium* and *Escherichia coli* bacterial strains, as well as with cultured mammalian cells such as the Chinese hamster cell ovary cells (HGPRT assay) with and without metabolic activation. In addition, several types of in vitro chromosomal aberration tests have been performed (chromosome aberration frequency in Chinese hamster ovary and lung cells, sister chromatid exchange in CHO cells). Results were negative both with and without metabolic activation for all category members. For the supporting chemical 1,2,3-TMB, a single in vitro chromosome aberration test was weakly positive. In in vivo bone marrow cytogenetics test, rats were exposed to C9 aromatic naphtha at concentrations of 0, 153, 471, or 1540 ppm (0, 750, 2,310, or 7,560 mg/m<sup>3</sup>) 6 hr/day, for 5 days. No evidence of in vivo somatic cell genotoxicity was detected. Based on the cumulative results of these assays, genetic toxicity is unlikely for substances in the C9 Aromatic Hydrocarbon Solvents Category.

#### Reproductive and Developmental Toxicity

Results from the three-generation reproduction inhalation study in rats indicate limited effects from C9 aromatic naphtha. In each of three generations (F0, F1 and F2), rats were exposed to High Flash Aromatic Naphtha (CAS RN 64742-95-6) via whole body inhalation at target concentrations of 0, 100, 500, or 1500 ppm (actual mean concentrations throughout the full study period were 0, 103, 495, or 1480 ppm, equivalent to 0, 505, 2430, or 7265 mg/m<sup>3</sup>, respectively). In each generation, both sexes were exposed for 10 weeks prior to and two weeks during mating for 6 hrs/day, 5 days/wks. Female rats in the F0, F1, and F2 generation were then exposed during gestation days 0-20 and lactation days 5-21 for 6 hrs/day, 7 days/wk. The age at exposure initiation differed among generations; F0 rats were exposed starting at 9 weeks of age, F1 exposure began at 5-7 weeks, and F2 exposure began at postnatal day (PND) 22. In the F0 and F1 parental generations, 30 rats/sex/group were exposed and mated. However, in the F2 generation, 40/sex/group were initially exposed due to concerns for toxicity, and 30/sex/group were randomly selected for mating, except that all survivors were used at 1480 ppm. F3 litters were not exposed directly and were sacrificed on lactation day 21.

#### Systemic Effects on Parental Generations:

The F0 males showed statistically and biologically significantly decreased mean body weight by ~15% at 1480 ppm when compared with controls. Seven females died or were sacrificed in extremis at 1480 ppm. The F0 female rats in the 495 ppm exposed group had a 13% decrease in body weight gain when adjusted for initial body weight when compared to controls. The F1 parents at 1480 ppm had statistically significantly decreased mean body weights (by ~13% (females) and 22% (males)), and locomotor activity. F1 parents at 1480 ppm had increased ataxia and mortality (six females). Most F2 parents (70/80) exposed to 1480 ppm died within the first week. The remaining animals survived throughout the rest of the exposure period. At week 4 and continuing through the study, F2 parents at 1480 ppm had statistically significant mean body weights much lower than controls (~33% for males; ~28% for females); body weights at 495 ppm were also reduced significantly (by 13% in males and 15% in females). The male rats in the 495 ppm exposed group had a 12% decrease in body weight gain when adjusted for initial body weight when compared to controls. Based on reduced body weight observed, the overall systemic toxicity LOAEC is 495 ppm (2430 mg/m<sup>3</sup>).

**Reproductive Toxicity-Effects on Parental Generations:** There were no pathological changes noted in the reproductive organs of any animal of the F0, F1, or F2 generation. No effects were reported on sperm morphology, gestational period, number of implantation sites, or post-implantation loss in any generation. Also, there were no statistically or biologically significant differences in any of the reproductive parameters, including: number of mated females, copulatory index, copulatory interval, number of females delivering a litter, number of females delivering a live litter, or male fertility in the F0 or in the F2 generation. Male fertility was statistically significantly reduced at 1480 ppm in the F1 rats. However, male fertility was not affected in the F0 or in the F2 generations; therefore, the biological significance of this change is unknown and may or may not be attributed to the test substance. No reproductive effects were observed in the F0 or F1 dams exposed to 1480 ppm (7265 mg/m<sup>3</sup>). Due to excessive mortality at the highest concentration (1480 ppm, only six dams available) in the F2 generation, a complete evaluation is precluded. However, no clear signs of reproductive toxicity were observed in the F2 generation. Therefore, the reproductive NOAEC is considered 495 ppm (2430 mg/m<sup>3</sup>), which excludes analysis of the highest concentration due to excessive mortality.

**Developmental Toxicity - Effects on Pups:** Because of significant maternal toxicity (including mortality) in dams in all generations at the highest concentration (1480 ppm), effects in offspring at 1480 ppm are not reported here. No significant effects were observed in the F1 and F2 generation offspring at 103 or 495 ppm. However, in F3 offspring, body weights and body weight gain were reduced by ~ 10-11% compared with controls at 495 ppm for approximately a week (PND 14 through 21). Maternal body weight was also depressed by ~ 12% throughout the gestational period compared with controls. The overall developmental LOAEC from this study is 495 ppm (2430 mg/m<sup>3</sup>) based on the body weights reductions observed in the F3 offspring.

**Conclusion:** No effects on reproductive parameters were observed at any exposure concentration, although a confident assessment of the group exposed at the highest concentration was not possible. A potential developmental effect (reduction in mean pup weight and weight gain) was observed at a

## ColorSpec Acrylic Clear Coat 1 Litre

|  |  |
|--|--|
|  | concentration that was also associated with maternal toxicity.<br>Inhalation (rat) TCLo: 1320 ppm/6h/90D-I * [Devoe]   |
| <b>ETHYL-3-ETHOXYPROPIONATE</b>                                    | * Union Carbide ** Endura Manufacturing  |
| <b>TOLUENE &amp; XYLENE &amp; N-BUTYL ACETATE &amp; ISOBUTANOL</b> | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. |
| <b>XYLENE &amp; N-BUTYL ACETATE &amp; ISOBUTANOL</b>               | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.   |
| <b>XYLENE &amp; BUTYL BENZYL PHTHALATE</b>                         | The substance is classified by IARC as Group 3:<br><b>NOT</b> classifiable as to its carcinogenicity to humans.<br>Evidence of carcinogenicity may be inadequate or limited in animal testing.   |
| <b>ACETONE &amp; ETHYL-3-ETHOXYPROPIONATE</b>                      | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.     |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✓ | <b>Carcinogenicity</b>          | ⊘ |
| <b>Skin Irritation/Corrosion</b>         | ✓ | <b>Reproductivity</b>           | ✓ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ⊘ | <b>STOT - Repeated Exposure</b> | ✓ |
| <b>Mutagenicity</b>                      | ⊘ | <b>Aspiration Hazard</b>        | ⊘ |

**Legend:** ✗ – Data available but does not fill the criteria for classification  
 ✓ – Data available to make classification  
 ⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| ColorSpec Acrylic Clear Coat 1 Litre                    | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|---|---------------|--------------------|-------------------------------|---------------|---------------|
|   | Not Available | Not Available      | Not Available                 | Not Available | Not Available |
| toluene   | LC50          | 96                 | Fish                          | 0.0073mg/L    | 4             |
|   | EC50          | 48                 | Crustacea                     | 3.78mg/L      | 5             |
|   | EC50          | 72                 | Algae or other aquatic plants | 12.5mg/L      | 4             |
|   | BCF           | 24                 | Algae or other aquatic plants | 10mg/L        | 4             |
|   | NOEC          | 168                | Crustacea                     | 0.74mg/L      | 5             |
| propylene glycol monomethyl ether acetate, alpha-isomer | LC50          | 96                 | Fish                          | =100mg/L      | 1             |
|   | EC50          | 48                 | Crustacea                     | =408mg/L      | 1             |
|   | EC0           | 24                 | Crustacea                     | =500mg/L      | 1             |
|   | NOEC          | 336                | Fish                          | 47.5mg/L      | 2             |
| xylene  | LC50          | 96                 | Fish                          | 2.6mg/L       | 2             |
|   | EC50          | 48                 | Crustacea                     | >3.4mg/L      | 2             |
|   | EC50          | 72                 | Algae or other aquatic plants | 4.6mg/L       | 2             |
|   | NOEC          | 73                 | Algae or other aquatic plants | 0.44mg/L      | 2             |
| acetone   | LC50          | 96                 | Fish                          | >100mg/L      | 4             |
|   | EC50          | 48                 | Crustacea                     | >100mg/L      | 4             |
|   | EC50          | 96                 | Algae or other aquatic plants | 20.565mg/L    | 4             |
|   | NOEC          | 96                 | Algae or other aquatic plants | 4.950mg/L     | 4             |
| n-butyl acetate   | LC50          | 96                 | Fish                          | 18mg/L        | 4             |
|   | EC50          | 48                 | Crustacea                     | =32mg/L       | 1             |
|   | EC50          | 72                 | Algae or other aquatic plants | =674.7mg/L    | 1             |
|   | EC0           | 192                | Algae or other aquatic plants | =21mg/L       | 1             |



## ColorSpec Acrylic Clear Coat 1 Litre

|   | ENDPOINT | TEST DURATION (HR)            | SPECIES                       | VALUE        | SOURCE |
|---|----------|-------------------------------|-------------------------------|--------------|--------|
| isobutanol                                | LC50     | 96                            | Fish                          | =1328.18mg/L | 4      |
|   | EC50     | 48                            | Crustacea                     | ca.600mg/L   | 1      |
|   | EC50     | 72                            | Algae or other aquatic plants | 593mg/L      | 2      |
|   | NOEC     | 504                           | Crustacea                     | 4mg/L        | 4      |
| butyl benzyl phthalate                    | ENDPOINT | TEST DURATION (HR)            | SPECIES                       | VALUE        | SOURCE |
|   | LC50     | 96                            | Fish                          | 0.51mg/L     | 4      |
|   | EC50     | 48                            | Crustacea                     | 0.017mg/L    | 4      |
|   | EC50     | 96                            | Algae or other aquatic plants | 0.1mg/L      | 4      |
|   | BCF      | 78.48                         | Fish                          | 0.034mg/L    | 4      |
| NOEC                                      | 336      | Algae or other aquatic plants | <0.02mg/L                     | 1            |        |
| naphtha petroleum, light aromatic solvent | ENDPOINT | TEST DURATION (HR)            | SPECIES                       | VALUE        | SOURCE |
|   | EC50     | 48                            | Crustacea                     | =6.14mg/L    | 1      |
|   | EC50     | 72                            | Algae or other aquatic plants | 3.29mg/L     | 1      |
|   | EC10     | 72                            | Algae or other aquatic plants | 1.13mg/L     | 1      |
| NOEC                                      | 72       | Algae or other aquatic plants | =1mg/L                        | 1            |        |
| ethyl-3-ethoxypropionate                  | ENDPOINT | TEST DURATION (HR)            | SPECIES                       | VALUE        | SOURCE |
|   | LC50     | 96                            | Fish                          | 45.3mg/L     | 2      |
|   | EC50     | 48                            | Crustacea                     | >95mg/L      | 1      |
|   | EC50     | 72                            | Algae or other aquatic plants | >114.86mg/L  | 2      |
| NOEC                                      | 48       | Crustacea                     | =9.5mg/L                      | 1            |        |

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and/or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and/or delayed, to the structure and/or functioning of natural ecosystems.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

for propylene glycol ethers:

**Environmental fate:**

Most are liquids at room temperature and all are water-soluble.

Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM)

Environmental fate: Log octanol-water partition coefficients (log Kow's) range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants, which indicate propensity to partition from water to air, are low for all category members, ranging from 5.7 x 10<sup>-9</sup> atm-m<sup>3</sup>/mole for TPM to 2.7 x 10<sup>-9</sup> atm-m<sup>3</sup>/mole for PnB. Fugacity modeling indicates that most propylene glycol ethers are likely to partition roughly equally into the soil and water compartments in the environment with small to negligible amounts remaining in other environmental compartments (air, sediment, and aquatic biota). Propylene glycol ethers are unlikely to persist in the environment. Once in air, the half-life of the category members due to direct reactions with photochemically generated hydroxyl radicals, range from 2.0 hours for TPM to 4.6 hours for PnB. In water, most members of this family are "readily biodegradable" under aerobic conditions. (DPMA degraded within 28 days (and within the specified 10-day window) but only using pre-adapted or "acclimated" inoculum.). In soil, biodegradation is rapid for PM and PMA.

**Ecotoxicity:**

Acute aquatic toxicity testing indicates low toxicity for both ethers and acetates. For ethers, effect concentrations are > 500 mg/L. For acetates, effect concentrations are > 151 mg/L.

Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus. For example, there is an increase in toxicity as alkylation of the naphthalene structure increases. The order of most toxic to least in a study using grass shrimp (*Palaemonetes pugio*) and brown shrimp (*Penaeus aztecus*) was dimethylnaphthalenes > methylnaphthalenes > naphthalenes.

Studies conclude that the toxicity of an oil appears to be a function of its di-aromatic and tri-aromatic hydrocarbons, which includes three-ring hydrocarbons such as phenanthrene.

The heavier (4-, 5-, and 6-ring) PAHs are more persistent than the lighter (2- and 3-ring) PAHs and tend to have greater carcinogenic and other chronic impact potential. PAHs in general are more frequently associated with chronic risks. These risks include cancer and often are the result of exposures to complex mixtures of chronic-risk aromatics (such as PAHs, alkyl PAHs, benzenes, and alkyl benzenes), rather than exposures to low levels of a single compound.

Anthracene is a phototoxic PAH. UV light greatly increases the toxicity of anthracene to bluegill sunfish. Benchmarks developed in the absence of UV light may be under-protective, and biological resources in strong sunlight are at more risk than those that are not.

For butyl benzyl phthalate (BBP)

log Kow : 4.78-4.91

Half-life (hr) air : 24-120

Henry's atm m<sup>3</sup>/mol: 1.30E-06

BCF : 663

**Environmental fate:**

**Terrestrial Fate:** A measured soil adsorption constant for BBP is 68-350; thus if released to land it will sorb to soil and should not leach appreciably, although it has been detected in ground water. The most significant fate process for BBP in soil will be biodegradation. Because of its low volatility, evaporation of BBP from soil is not expected to be significant.

**Aquatic Fate:** BBP has a log Kow of 4.77. Thus, BBP released to waters will partition to solids such as sediment and biota. The primary fate mechanism for BBP will be biodegradation. At an initial concentration of 1 mg/L in a lake water microcosm, primary degradation accounted for >95% loss of BBP in 7 days; after 28 days, 51-65% of it had mineralized (ultimate degradation). Based on the estimated Henry's Law constant, volatilization of BBP from water will not be significant except from shallow rivers or during high wind activity. Photodegradation and hydrolysis will not be significant, since the half-lives for these processes are >100 days.

**Atmospheric Fate:** BBP released to the atmosphere has an estimated half-life of 1-5 days. However, volatilization of BBP to the atmosphere is not expected to be a significant transport mechanism, since its vapor pressure is only 8.6 x 10<sup>-6</sup> mm Hg at 20 C and its Henry's Law constant is <1.0 x 10<sup>-6</sup> atm/mol m<sup>3</sup>

**Ecotoxicity:**

Fish LC50 (96 h): 1.7-43 mg/L

Invertebrate LC50 (96 h): 3.7 mg/L

Bioaccumulation : little

Anaerobic effects : sig degrad

Effects on algae and plankton: LC50(96)0.4-1mg/L

Degradation Biological: sig

processes Abiotic: not sig

For xylenes :

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H<sub>2</sub>O surface water : 24-672

Half-life (hr) H<sub>2</sub>O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m<sup>3</sup>/mol: 637-879

Henry's atm m<sup>3</sup>/mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

#### Environmental Fate

**Terrestrial fate:** Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. Volatilisation of p-xylene is expected to be important from moist soil surfaces given a measured Henry's Law constant of  $7.18 \times 10^{-3}$  atm-cu m/mole. The potential for volatilisation of 3-xylene from dry soil surfaces may exist based on a measured vapor pressure of 8.29 mm Hg. p-Xylene may be degraded during its passage through soil). The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. p-Xylene, present in soil samples contaminated with jet fuel, was completely degraded aerobically within 5 days. In aquifer studies under anaerobic conditions, p-xylene was degraded, usually within several weeks, with the production of 3-methylbenzylfumaric acid, 3-methylbenzylsuccinic acid, 3-methylbenzoate, and 3-methylbenzaldehyde as metabolites.

**Aquatic fate:** Koc values indicate that p-xylene may adsorb to suspended solids and sediment in water. p-Xylene is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. BCF values of 14.8, 23.4, and 6, measured in goldfish, eels, and clams, respectively, indicate that bioconcentration in aquatic organisms is low. p-Xylene in water with added humic substances was 50% degraded following 3 hours irradiation suggesting that indirect photooxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. Although p-xylene is biodegradable and has been observed to degrade in pond water, there are insufficient data to assess the rate of this process in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater in several studies; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high.

#### Atmospheric fate:

Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere primarily by reaction with photochemically-produced hydroxyl radicals, with an estimated atmospheric lifetime of about 0.5 to 2 days. Xylenes' susceptibility to photochemical oxidation in the troposphere is to the extent that they may contribute to photochemical smog formation.

According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere and from its vapour pressure, p-xylene, is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase p-xylene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 16 hours. A half-life of 1.0 hr in summer and 10 hr in winter was measured for the reaction of p-xylene with photochemically-produced hydroxyl radicals. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers, with loss rates varying from 9-42% per hr. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzyl nitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-dimethylphenol, and 4-nitro-2,6-dimethylphenol.

#### Ecotoxicity:

for xylenes

Fish LC50 (96 h) Pimephales promelas 13.4 mg/l; Oncorhynchus mykiss 8.05 mg/l; Lepomis macrochirus 16.1 mg/l (all flow through values); Pimephales promelas 26.7 (static)

Daphnia EC50 948 h): 3.83 mg/l

Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/l

Gammarus lacustris LC50 (48 h): 0.6 mg/l

#### For ketones:

Ketones, unless they are alpha, beta-unsaturated ketones, can be considered as narcosis or baseline toxicity compounds

Hydrolysis may also involve the addition of water to ketones to yield ketals under mild acid conditions. However, this addition of water is thermodynamically favorable only for low molecular weight ketones. This addition is an equilibrium reaction that is reversible upon a change of water concentration and the reaction ultimately leads to no permanent change in the structure of the ketone substrate. The higher molecular weight ketones do not form stable ketals. Therefore, the ketones are stable to water under ambient environmental conditions

Another possible reaction of ketones in water involves the enolic hydrogen on the carbons bonded to the carbonyl function. Under conditions of high pH (pH greater than 10), the enolic proton is abstracted by base (OH<sup>-</sup>) forming a carbanion intermediate that may react with other organic substrates (e.g., ketones, esters, aldehydes) containing a center for nucleophilic attack. The reactions, commonly recognized as condensation reactions, produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavorable.

Based on its reactions in air, it seems likely that ketones undergo photolysis in water. It is probable that ketones will be biodegraded to an appreciable degree by micro-organisms in soil and water. They are unlikely to bioconcentrate or biomagnify.

For toluene:

log Kow : 2.1-3

log Koc : 1.12-2.85

Koc : 37-260

log Kom : 1.39-2.89

Half-life (hr) air : 2.4-104

Half-life (hr) H<sub>2</sub>O surface water : 5.55-528

Half-life (hr) H<sub>2</sub>O ground : 168-2628

Half-life (hr) soil : <48-240

Henry's Pa m<sup>3</sup>/mol: 518-694

Henry's atm m<sup>3</sup>/mol: 5.94E-03

BOD 5 0.86-2.12, 5%

COD : 0.7-2.52, 21-27%

ThOD : 3.13

BCF : 1.67-380

log BCF : 0.22-3.28

#### Environmental fate:

**Transport:** The majority of toluene evaporates to the atmosphere from the water and soil. It is moderately retarded by adsorption to soils rich in organic material (Koc = 259), therefore, transport to ground water is dependent on the soil composition. In unsaturated topsoil containing organic material, it has been estimated that 97% of the toluene is adsorbed to the soil and only about 2% is in the soil-water phase and transported with flowing groundwater. There is little retardation in sandy soils and 2-13% of the toluene was estimated to migrate with flowing water; the remainder was volatilised, biodegraded, or unaccounted for. In saturated deep soils with no soil-air phase, about 48% may be transported with flowing groundwater.

#### Transformation/Persistence:

**Air** - The main degradation pathway for toluene in the atmosphere is reaction with photochemically produced hydroxyl radicals. The estimated atmospheric half life for toluene is about 13 hours. Toluene is also oxidised by reactions with atmospheric nitrogen dioxide, oxygen, and ozone, but these are minor degradation pathways. Photolysis is not considered a significant degradative pathway for toluene

**Soil** - In surface soil, volatilisation to air is an important fate process for toluene. Biodegradation of toluene has been demonstrated in the laboratory to occur with a half life of about 1 hour. In the environment, biodegradation of toluene to carbon dioxide occurs with a typical half life of 1-7 days.

**Water** - An important fate process for toluene is volatilization, the rate of which depends on the amount of turbulence in the surface water. The volatilisation of toluene from static water has a half life of 1-16 days, whereas from turbulent water the half life is 5-6 hours. Degradation of toluene in surface water occurs primarily by biodegradation with a half life of less than one day under favorable conditions (presence of microorganisms, microbial adaptation, and optimum temperature). Biodegradation also occurs in shallow groundwater and in salt water at a reduced rate). No

data are available on anaerobic degradation of toluene in deep ground water conditions where aerobic degradation would be minimal.

**Biota** - Bioaccumulation in most organisms is limited by the metabolism of toluene into more polar compounds that have greater water solubility and a lower affinity for lipids. Bioaccumulation in the food chain is predicted to be low.

**Ecotoxicity:**

Toluene has moderate acute toxicity to aquatic organisms; several toxicity values are in the range of greater than 1 mg/L and 100 mg/L.

Fish LC50 (96 h): fathead minnow (*Pimephales promelas*) 12.6-72 mg/l; *Lepomis macrochirus* 13-24 mg/l;

guppy (*Poecilia reticulata*) 28.2-59.3 mg/l; channel catfish (*Ictalurus punctatus*) 240 mg/l; goldfish (*Carassius auratus*): 22.8-57.68 mg/l

Crustaceans LC50 (96 h): grass shrimp (*Palaemonetes pugio*) 9.5 ppm, crab larvae stage (*Cancer magister*) 28 ppm; shrimp (*Crangon franciscorum*) 4.3 ppm; daggerblade grass

shrimp (*Palaemonetes pugio*) 9.5 mg/l

Algae EC50 (24 h): green algae (*Chlorella vulgaris*) 245 mg/l (growth); (72 h) green algae (*Selenastrum capricornutum*) 12.5 mg/l (growth)

For n-butyl acetate:

Half-life (hr) air : 144

Half-life (hr) H2O surface water : 178-27156

Henry's atm m3/mol: 3.20E-04

BOD 5 if unstated: 0.15-1.02,7%

COD : 78%

ThOD : 2.207

BCF : 4-14

**Environmental Fate:**

**TERRESTRIAL FATE:** An estimated Koc value of 200 determined from a measured log Kow of 1.78 indicates that n-butyl acetate is expected to have moderate mobility in soil. Volatilisation of n-butyl acetate is expected from moist soil surfaces given its Henry's Law constant of  $2.8 \times 10^{-4}$  atm-cu m/mole. Volatilisation from dry soil surfaces is expected based on a measured vapor pressure of 11.5 mm Hg. Using a standard BOD dilution technique and a sewage inoculum, theoretical BODs of 56 % to 86 % were observed during 5-20 day incubation periods, which suggests that n-butyl acetate may biodegrade in soil.

**AQUATIC FATE:** An estimated Koc value indicates that n-butyl acetate is not expected to adsorb to suspended solids and sediment in water. Butyl acetate is expected to volatilise from water surfaces based on a Henry's Law constant of  $2.8 \times 10^{-4}$  atm-cu m/mole. Estimated half-lives for a model river and model lake are 7 and 127, hours respectively. An estimated BCF value of 10 based on the log Kow, suggests that bioconcentration in aquatic organisms is low. Using a filtered sewage seed, 5-day and 20-day theoretical BODs of 58 % and 83 % were measured in freshwater dilution tests; 5-day and 20-day theoretical BODs of 40 % and 61 % were measured in salt water. A 5-day theoretical BOD of 56.8 % and 51.8 % were measured for n-butyl acetate in distilled water and seawater, respectively. Hydrolysis may be an important environmental fate for this compound based upon experimentally determined hydrolysis half-lives of 114 and 11 days at pH 8 and 9 respectively.

**ATMOSPHERIC FATE:** According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere, n-butyl acetate, which has a vapour pressure of 11.5 mm Hg at 25 deg C, is expected to exist solely as a vapor in the ambient atmosphere. Vapour-phase n-butyl acetate is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 4 days

**Environmental fate:**

Fish LC50 (96 h, 23 C): island silverside (*Menidia beryllina*) 185 ppm (static bioassay in synthetic seawater, mild aeration applied after 24 h); bluegill sunfish (*Lepomis macrochirus*) 100 ppm (static bioassay in fresh water, mild aeration applied after 24 h)

Fish EC50 (96 h): fathead minnow (*Pimephales promelas*) 18 mg/l (affected fish lost equilibrium prior to death)

Daphnia LC50 (48 h): 44 ppm

Algal LC50 (96 h): *Scenedesmus* 320 ppm

for acetone:

log Kow: -0.24

Half-life (hr) air: 312-1896

Half-life (hr) H2O surface water: 20

Henry's atm m3/mol: 3.67E-05

BOD 5: 0.31-1.76,46-55%

COD: 1.12-2.07

ThOD: 2.2

BCF: 0.69

**Environmental fate:**

Acetone preferentially locates in the air compartment when released to the environment. A substantial amount of acetone can also be found in water, which is consistent with the high water to air partition coefficient and its small, but detectable, presence in rain water, sea water, and lake water samples. Very little acetone is expected to reside in soil, biota, or suspended solids. This is entirely consistent with the physical and chemical properties of acetone and with measurements showing a low propensity for soil absorption and a high preference for moving through the soil and into the ground water

In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days. The relatively long half-life allows acetone to be transported long distances from its emission source.

Acetone is highly soluble and slightly persistent in water, with a half-life of about 20 hours; it is minimally toxic to aquatic life.

Acetone released to soil volatilises although some may leach into the ground where it rapidly biodegrades.

Acetone does not concentrate in the food chain.

Acetone meets the OECD definition of readily biodegradable which requires that the biological oxygen demand (BOD) is at least 70% of the theoretical oxygen demand (THOD) within the 28-day test period

Drinking Water Standard: none available.

Soil Guidelines: none available.

Air Quality Standards: none available.

**Ecotoxicity:**

Testing shows that acetone exhibits a low order of toxicity

Fish LC50: brook trout 6070 mg/l; fathead minnow 15000 mg/l

Bird LC0 (5 day): Japanese quail, ring-neck pheasant 40,000 mg/l

Daphnia magna LC50 (48 h): 15800 mg/l; NOEC 8500 mg/l

Aquatic invertebrate 2100 - 16700 mg/l

Aquatic plant NOEC: 5400-7500 mg/l

Daphnia magna chronic NOEC 1660 mg/l

Acetone vapors were shown to be relatively toxic to two types insects and their eggs. The time to 50% lethality (LT50) was found to be 51.2 hr and 67.9 hr when the flour beetle (*Tribolium confusum*) and the flour moth (*Ephestia kuehniella*) were exposed to an airborne acetone concentration of 61.5 mg/m3. The LT50 values for the eggs were 30-50% lower than for the adult. The direct application of acetone liquid to the body of the insects or surface of the eggs did not, however, cause any mortality.

The ability of acetone to inhibit cell multiplication has been examined in a wide variety of microorganisms. The results have generally indicated mild to minimal toxicity with NOECs greater than 1700 mg/L for exposures lasting from 6 hr to 4 days. Longer exposure periods of 7 to 8 days with bacteria produced mixed results; but overall the data indicate a low degree of toxicity for acetone.

The only exception to these findings were the results obtained with the flagellated protozoa (*Entosiphon sulcatum*) which yielded a 3-day NOEC of 28 mg/L.

**DO NOT discharge into sewer or waterways.**

**Persistence and degradability**

| Ingredient  | Persistence: Water/Soil     | Persistence: Air            |
|---|-----------------------------|-----------------------------|
| toluene   | LOW (Half-life = 28 days)   | LOW (Half-life = 4.33 days) |
| propylene glycol monomethyl ether acetate, alpha-isomer | LOW                         | LOW                         |
| xylene  | HIGH (Half-life = 360 days) | LOW (Half-life = 1.83 days) |

|                          |                              |                                  |
|--------------------------|------------------------------|----------------------------------|
| acetone                  | LOW (Half-life = 14 days)    | MEDIUM (Half-life = 116.25 days) |
| n-butyl acetate          | LOW                          | LOW                              |
| isobutanol               | LOW (Half-life = 14.42 days) | LOW (Half-life = 4.15 days)      |
| butyl benzyl phthalate   | HIGH (Half-life = 180 days)  | LOW (Half-life = 2.5 days)       |
| ethyl-3-ethoxypropionate | LOW                          | LOW                              |

**Bioaccumulative potential**

| Ingredient  | Bioaccumulation       |
|---|-----------------------|
| toluene   | LOW (BCF = 90)        |
| propylene glycol monomethyl ether acetate, alpha-isomer | LOW (LogKOW = 0.56)   |
| xylene  | MEDIUM (BCF = 740)    |
| acetone   | LOW (BCF = 0.69)      |
| n-butyl acetate   | LOW (BCF = 14)        |
| isobutanol  | LOW (LogKOW = 0.76)   |
| butyl benzyl phthalate                                  | MEDIUM (BCF = 663)    |
| ethyl-3-ethoxypropionate                                | LOW (LogKOW = 1.0809) |

**Mobility in soil**

| Ingredient  | Mobility             |
|---|----------------------|
| toluene   | LOW (KOC = 268)      |
| propylene glycol monomethyl ether acetate, alpha-isomer | HIGH (KOC = 1.838)   |
| acetone   | HIGH (KOC = 1.981)   |
| n-butyl acetate   | LOW (KOC = 20.86)    |
| isobutanol  | MEDIUM (KOC = 2.048) |
| butyl benzyl phthalate                                  | LOW (KOC = 9359)     |
| ethyl-3-ethoxypropionate                                | LOW (KOC = 10)       |

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|--|

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

|                  |   |
|------------------|---|
| Marine Pollutant |  |
| HAZCHEM          | *3YE  |

**Land transport (ADG)**

|                              |  |
|------------------------------|--|
| UN number                    | 1263   |
| UN proper shipping name      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Transport hazard class(es)   | Class : 3<br>Subrisk : Not Applicable  |
| Packing group                | II   |
| Environmental hazard         | Environmentally hazardous  |
| Special precautions for user | Special provisions : 163 367<br>Limited quantity : 5 L   |

**Air transport (ICAO-IATA / DGR)**

|                              |   |
|------------------------------|---|
| UN number                    | 1263  |
| UN proper shipping name      | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)   |
| Transport hazard class(es)   | ICAO/IATA Class : 3<br>ICAO / IATA Subrisk : Not Applicable<br>ERG Code : 3L  |
| Packing group                | II  |
| Environmental hazard         | Environmentally hazardous   |
| Special precautions for user | Special provisions : A3 A72 A192<br>Cargo Only Packing Instructions : 364<br>Cargo Only Maximum Qty / Pack : 60 L<br>Passenger and Cargo Packing Instructions : 353<br>Passenger and Cargo Maximum Qty / Pack : 5 L<br>Passenger and Cargo Limited Quantity Packing Instructions : Y341<br>Passenger and Cargo Limited Maximum Qty / Pack : 1 L |

**Sea transport (IMDG-Code / GGVSee)**

|                              |  |
|------------------------------|--|
| UN number                    | 1263   |
| UN proper shipping name      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Transport hazard class(es)   | IMDG Class : 3<br>IMDG Subrisk : Not Applicable  |
| Packing group                | II   |
| Environmental hazard         | Marine Pollutant   |
| Special precautions for user | EMS Number : F-E , S-E<br>Special provisions : 163 367<br>Limited Quantities : 5 L   |

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****TOLUENE(108-88-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER(108-65-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Continued...

|  |   |
|--|---|
| Australia Exposure Standards<br>Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

**XYLENE(1330-20-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|  |  |
|--|--|
| Australia Exposure Standards<br>Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS)<br>International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |
|--|--|

**ACETONE(67-64-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|  |   |
|--|---|
| Australia Exposure Standards<br>Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

**N-BUTYL ACETATE(123-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|  |   |
|--|---|
| Australia Exposure Standards<br>Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

**ISOBUTANOL(78-83-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|  |   |
|--|---|
| Australia Exposure Standards<br>Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

**BUTYL BENZYL PHTHALATE(85-68-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|   |   |
|---|---|
| Australia Hazardous Substances Information System - Consolidated Lists<br>Australia Inventory of Chemical Substances (AICS) | International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |
|---|---|

**NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT(64742-95-6.) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|  |   |
|--|---|
| Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

**ETHYL-3-ETHOXYPROPIONATE(763-69-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

|   |
|---|
| Australia Inventory of Chemical Substances (AICS) |
|---|

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (toluene; propylene glycol monomethyl ether acetate, alpha-isomer; acetone; xylene; n-butyl acetate; naphtha petroleum, light aromatic solvent; ethyl-3-ethoxypropionate; isobutanol; butyl benzyl phthalate) |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | Y   |
| Japan - ENCS                  | Y   |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)                        |

**SECTION 16 OTHER INFORMATION****Other information****Ingredients with multiple cas numbers**

| Name  | CAS No                            |
|---|-----------------------------------|
| propylene glycol monomethyl ether acetate, alpha-isomer | 108-65-6, 84540-57-8, 142300-82-1 |
| naphtha petroleum, light aromatic solvent               | 64742-95-6., 25550-14-5.          |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC— TWA: Permissible Concentration-Time Weighted Average  
 PC— STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.