

# Colorspec Plastic Primer

## Motor Active

Chemwatch: 40-9389  
Version No: 3.1.1.1  
Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 23/06/2016  
Print Date: 23/06/2016  
Initial Date: **Not Available**  
S.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	Colorspec Plastic Primer
Synonyms	Product Code: CSPP400G
Proper shipping name	AEROSOLS
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Use according to manufacturer's directions. Aerosol for industrial and commercial use.
--------------------------	--

### Details of the supplier of the safety data sheet

Registered company name	Motor Active
Address	35 Slough Business Park, Holker Street Silverwater NSW 2128 Australia
Telephone	+61 2 9737 9422 1800 350 622
Fax	+61 2 9737 9414
Website	www.motoractive.com.au
Email	andrew.spira@motoractive.com.au

### Emergency telephone number

Association / Organisation	MotorActive
Emergency telephone numbers	+61 2 9737 9422 (For General Information Monday to Friday 8:30am to 5:pm)
Other emergency telephone numbers	13 11 26 (In Case of Emergency contact: Poison Information Hotline)

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code.


#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	4	
Toxicity	2	
Body Contact	2	
Reactivity	1	
Chronic	3	

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Poisons Schedule	Not Applicable
Classification [1]	Aerosols Category 1, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Reproductive Toxicity Category 1B, Specific target organ toxicity - single exposure Category 3 (narcotic effects), Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

### Label elements

GHS label elements	
SIGNAL WORD	<b>DANGER</b>

### Hazard statement(s)

H222	Extremely flammable aerosol.
------	------------------------------

Continued...

H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
AUH044	Risk of explosion if heated under confinement
AUH066	Repeated exposure may cause skin dryness and cracking

**Supplementary statement(s)**

Not Applicable

**CLP classification (additional)**

Not Applicable

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.

**Precautionary statement(s) Response**

P308+P313	IF exposed or concerned: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.

**Precautionary statement(s) Storage**

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container in accordance with local regulations.
------	---

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
123-86-4	10-30	<u>n-butyl acetate</u>
67-64-1	10-25	<u>acetone</u>
1330-20-7	<10	<u>xylene</u>
14807-96-6	<10	<u>talc</u>
13463-67-7	<10	<u>titanium dioxide</u>
64-17-5	<10	<u>ethanol</u>
1317-65-3	<10	<u>limestone</u>
108-88-3	<5	<u>toluene</u>
85-68-7	<1	<u>butyl benzyl phthalate</u>
115-10-6	30-60	<u>dimethyl ether</u>

**SECTION 4 FIRST AID MEASURES****Description of first aid measures**

<b>Eye Contact</b>	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Remove any adhering solids with industrial skin cleansing cream.</li> <li>▶ <b>DO NOT use solvents.</b></li> <li>▶ Seek medical attention in the event of irritation.</li> </ul>

## Colorespec Plastic Primer

<b>Inhalation</b>	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> </ul> <p>Not considered a normal route of entry.</p>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.  
for lower alkyl ethers:

#### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ A low-stimulus environment must be maintained.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

#### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension without signs of hypovolaemia may require vasopressors.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

#### EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Ethers may produce anion gap acidosis. Hyperventilation and bicarbonate therapy might be indicated.
- ▶ Haemodialysis might be considered in patients with impaired renal function.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

for simple esters:

#### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

#### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

#### EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> < 50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Continued...

## Colorespec Plastic Primer

- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Methylhippu-ric acids in urine	1.5 gm/gm creatinine 2 mg/min	End of shift Last 4 hrs of shift	

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

#### SMALL FIRE:

- ▶ Water spray, dry chemical or CO<sub>2</sub>

#### LARGE FIRE:

- ▶ Water spray or fog.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) hydrogen chloride phosgene hydrogen fluoride, nitrogen oxides (NO<sub>x</sub>) other pyrolysis products typical of burning organic material</p> <p><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Shut off all possible sources of ignition and increase ventilation.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove leaking cylinders to a safe place if possible.</li> <li>▶ Release pressure under safe, controlled conditions by opening the valve.</li> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong acids, bases.</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
--------	------------	---------------	-----	------	------	-------

Continued...

## Colorespec Plastic Primer


Australia Exposure Standards	n-butyl acetate	n-Butyl acetate	713 mg/m <sup>3</sup> / 150 ppm	950 mg/m <sup>3</sup> / 200 ppm	Not Available	Not Available
Australia Exposure Standards	acetone	Acetone	1185 mg/m <sup>3</sup> / 500 ppm	2375 mg/m <sup>3</sup> / 1000 ppm	Not Available	Not Available
Australia Exposure Standards	xylene	Xylene (o-, m-, p- isomers)	350 mg/m <sup>3</sup> / 80 ppm	655 mg/m <sup>3</sup> / 150 ppm	Not Available	Not Available
Australia Exposure Standards	talc	Soapstone (respirable dust) / Talc, (containing no asbestos fibres)	3 mg/m <sup>3</sup> / 2.5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	titanium dioxide	Titanium dioxide	10 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	ethanol	Ethyl alcohol	1880 mg/m <sup>3</sup> / 1000 ppm	Not Available	Not Available	Not Available
Australia Exposure Standards	limestone	Calcium carbonate	10 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	toluene	Toluene	191 mg/m <sup>3</sup> / 50 ppm	574 mg/m <sup>3</sup> / 150 ppm	Not Available	Sk
Australia Exposure Standards	dimethyl ether	Dimethyl ether	760 mg/m <sup>3</sup> / 400 ppm	950 mg/m <sup>3</sup> / 500 ppm	Not Available	Not Available

### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
n-butyl acetate	Butyl acetate, n-	Not Available	Not Available	Not Available
acetone	Acetone	Not Available	Not Available	Not Available
xylene	Xylenes	Not Available	Not Available	Not Available
talc	Talc	2 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>	2.6 mg/m <sup>3</sup>
titanium dioxide	Titanium oxide; (Titanium dioxide)	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
ethanol	Ethyl alcohol; (Ethanol)	Not Available	Not Available	Not Available
limestone	Limestone; (Calcium carbonate; Dolomite)	27 mg/m <sup>3</sup>	27 mg/m <sup>3</sup>	1300 mg/m <sup>3</sup>
limestone	Carbonic acid, calcium salt	45 mg/m <sup>3</sup>	210 mg/m <sup>3</sup>	1300 mg/m <sup>3</sup>
toluene	Toluene	Not Available	Not Available	Not Available
butyl benzyl phthalate	Phthalic acid, benzyl butyl ester; (Benzyl butyl phthalate)	15 mg/m <sup>3</sup>	20 mg/m <sup>3</sup>	460 mg/m <sup>3</sup>
dimethyl ether	Methyl ether; (Dimethyl ether)	1,000 ppm	1000 ppm	7200 ppm

Ingredient	Original IDLH	Revised IDLH
n-butyl acetate	10,000 ppm	1,700 [LEL] ppm
acetone	20,000 ppm	2,500 [LEL] ppm
xylene	1,000 ppm	900 ppm
talc	N.E. mg/m <sup>3</sup> / N.E. ppm	1,000 mg/m <sup>3</sup>
titanium dioxide	N.E. mg/m <sup>3</sup> / N.E. ppm	5,000 mg/m <sup>3</sup>
ethanol	15,000 ppm	3,300 [LEL] ppm
limestone	Not Available	Not Available
toluene	2,000 ppm	500 ppm
butyl benzyl phthalate	Not Available	Not Available
dimethyl ether	Not Available	Not Available

### Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> <li>▶ Close fitting gas tight goggles</li> </ul> <p><b>DO NOT wear contact lenses.</b></p> <ul style="list-style-type: none"> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.</li> </ul>
<b>Skin protection</b>	See Hand protection below

## Colorespec Plastic Primer

<b>Hands/feet protection</b>	<p>For esters:</p> <ul style="list-style-type: none"> <li>▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials.</li> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ <b>OTHERWISE:</b></li> <li>▶ For potentially moderate exposures:</li> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures:</li> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eyewash unit.</li> <li>▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.</li> <li>▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.</li> </ul> <p>BRETHERRICK: Handbook of Reactive Chemical Hazards.</p>
<b>Thermal hazards</b>	Not Available

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index"**.

The effect(s) of the following substance(s) are taken into account in the **computer-**

**generated** selection:

Colorespec Plastic Primer

Material	CPI
##n-butyl	acetate
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/BUTYL	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C
##dimethyl	ether
##butyl benzyl	phthalate

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS / Class 1 P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	Air-line*	-	-
up to 100 x ES	-	AX-3 P2	-
100+ x ES	-	Air-line**	-

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### Appearance

Supplied as an aerosol pack. Contents under **PRESSURE**. Contains highly flammable ether propellant.

Continued...

## Colorespec Plastic Primer

	Thin grey highly flammable liquid with a strong solvent odour.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.80-0.90
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	354
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	14-18 secs B4 Cup @25C
<b>Initial boiling point and boiling range (°C)</b>	-25 to 145	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	-41 (OC)	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Availa0.40-10.00 BuAC = 1	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	19	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	1	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	510 @20C	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Not Available	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

### SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

### SECTION 11 TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

<b>Inhaled</b>	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression. As a rule, these compounds may also act as general anaesthetics.</p> <p>Systemic poisoning produced by general anaesthesia is characterised by lightheadedness, nervousness, apprehension, euphoria, confusion, dizziness, drowsiness, tinnitus, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness and respiratory depression and arrest. Cardiac arrest may result from cardiovascular collapse.</p> <p>Inhalation of toxic gases may cause:</p> <ul style="list-style-type: none"> <li>▶ Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;</li> <li>▶ respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;</li> <li>▶ heart: collapse, irregular heartbeats and cardiac arrest;</li> <li>▶ gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.</li> </ul> <p>Following inhalation, ethers cause lethargy and stupor. Inhaling lower alkyl ethers results in headache, dizziness, weakness, blurred vision, seizures and possible coma.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p><b>WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.</b></p> <p>Headache, fatigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers.</p> <p>Xylene is a central nervous system depressant</p> <p>The main effects of simple esters are irritation, stupor and insensibility. Headache, drowsiness, dizziness, coma and behavioural changes may occur. Prolonged exposure may cause headache, nausea and ultimately loss of consciousness.</p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p> <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>Ingestion of alkyl ethers may produce stupor, blurred vision, headache, dizziness and irritation of the nose and throat. Respiratory distress and asphyxia may result.</p>

## Colorespec Plastic Primer

<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.          Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.          There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time.          Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.          Spray mist may produce discomfort          Alkyl ethers may defat and dehydrate the skin producing dermatoses. Absorption may produce headache, dizziness, and central nervous system depression.          Open cuts, abraded or irritated skin should not be exposed to this material</p>
<b>Eye</b>	<p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.          Not considered to be a risk because of the extreme volatility of the gas. Eye contact with alkyl ethers (vapour or liquid) may produce irritation, redness and tears.</p>
<b>Chronic</b>	<p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.          Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.          Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.          Principal route of occupational exposure to the gas is by inhalation.          Chronic exposure to alkyl ethers may result in loss of appetite, excessive thirst, fatigue, and weight loss.          Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.          Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.          There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.          Workers exposed to acetone for long periods showed inflammation of the airways, stomach and small bowel, attacks of giddiness and loss of strength. Exposure to acetone may enhance the liver toxicity of chlorinated solvents.</p>

Colorespec Plastic Primer	TOXICITY	IRRITATION
	Not Available	Not Available
<b>n-butyl acetate</b>	<p><b>TOXICITY</b></p> <p>Dermal (rabbit) LD50: &gt;14080 mg/kg<sup>[1]</sup></p> <p>Inhalation (rat) LC50: 2000 ppm/4hr<sup>[2]</sup></p> <p>Inhalation (rat) LC50: 390 ppm/4hr<sup>[2]</sup></p> <p>Oral (rat) LD50: 10736 mg/kg<sup>[1]</sup></p>	<p><b>IRRITATION</b></p> <p>* [PPG]</p> <p>Eye (human): 300 mg</p> <p>Eye (rabbit): 20 mg (open)-SEVERE</p> <p>Eye (rabbit): 20 mg/24h - moderate</p> <p>Skin (rabbit): 500 mg/24h-moderate</p>
<b>acetone</b>	<p><b>TOXICITY</b></p> <p>Dermal (rabbit) LD50: 20000 mg/kg<sup>[2]</sup></p> <p>Inhalation (rat) LC50: 50.1 mg/L/8 hr<sup>[2]</sup></p> <p>Oral (rat) LD50: 5800 mg/kg<sup>[2]</sup></p>	<p><b>IRRITATION</b></p> <p>Eye (human): 500 ppm - irritant</p> <p>Eye (rabbit): 20mg/24hr -moderate</p> <p>Eye (rabbit): 3.95 mg - SEVERE</p> <p>Skin (rabbit): 500 mg/24hr - mild</p> <p>Skin (rabbit):395mg (open) - mild</p>
<b>xylene</b>	<p><b>TOXICITY</b></p> <p>Dermal (rabbit) LD50: &gt;1700 mg/kg<sup>[2]</sup></p> <p>Inhalation (rat) LC50: 5000 ppm/4hr<sup>[2]</sup></p> <p>Oral (rat) LD50: 4300 mg/kg<sup>[2]</sup></p>	<p><b>IRRITATION</b></p> <p>Eye (human): 200 ppm irritant</p> <p>Eye (rabbit): 5 mg/24h SEVERE</p> <p>Eye (rabbit): 87 mg mild</p> <p>Skin (rabbit):500 mg/24h moderate</p>
<b>talc</b>	<p><b>TOXICITY</b></p> <p>Not Available</p>	<p><b>IRRITATION</b></p> <p>Skin (human): 0.3 mg/3d-I mild</p>
<b>titanium dioxide</b>	<p><b>TOXICITY</b></p> <p>Inhalation (rat) LC50: &gt;2.28 mg/l/4hr<sup>[1]</sup></p> <p>Inhalation (rat) LC50: &gt;3.56 mg/l/4hr<sup>[1]</sup></p> <p>Inhalation (rat) LC50: &gt;6.82 mg/l/4hr<sup>[1]</sup></p> <p>Inhalation (rat) LC50: 3.43 mg/l/4hr<sup>[1]</sup></p> <p>Inhalation (rat) LC50: 5.09 mg/l/4hr<sup>[1]</sup></p> <p>Oral (rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></p>	<p><b>IRRITATION</b></p> <p>Skin (human): 0.3 mg /3D (int)-mild *</p>
<b>ethanol</b>	<p><b>TOXICITY</b></p> <p>Dermal (rabbit) LD50: 17100 mg/kg<sup>[1]</sup></p> <p>Inhalation (rat) LC50: 64000 ppm/4hr<sup>[2]</sup></p> <p>Oral (rat) LD50: &gt;1187-2769 mg/kg<sup>[1]</sup></p>	<p><b>IRRITATION</b></p> <p>Eye (rabbit): 500 mg SEVERE</p> <p>Eye (rabbit):100mg/24hr-moderate</p> <p>Skin (rabbit):20 mg/24hr-moderate</p> <p>Skin (rabbit):400 mg (open)-mild</p>
<b>limestone</b>	<p><b>TOXICITY</b></p> <p>Oral (rat) LD50: 6450 mg/kg<sup>[2]</sup></p>	<p><b>IRRITATION</b></p> <p>Skin (rabbit): 500 mg/24h-moderate</p>



## Colorespec Plastic Primer

<b>toluene</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 12124 mg/kg <sup>[2]</sup>	Eye (rabbit): 2mg/24h - SEVERE
	Inhalation (rat) LC50: >26700 ppm/1hr <sup>[2]</sup>	Eye (rabbit): 0.87 mg - mild
	Inhalation (rat) LC50: 49 mg/L/4hr <sup>[2]</sup>	Eye (rabbit): 100 mg/30sec - mild
<b>butyl benzyl phthalate</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: 6700 mg/kg <sup>[2]</sup>	[BASF]*
	Oral (rat) LD50: 2330 mg/kg <sup>[2]</sup>	[MONSANTO]**
		Nil reported
<b>dimethyl ether</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation (rat) LC50: 309 mg/L/4hr <sup>[2]</sup>	Nil reported

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>Colorespec Plastic Primer</b>	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>for acetone: The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage.</p>
<b>ACETONE</b>	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>for acetone: The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage.</p>
<b>XYLENE</b>	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Reproductive effector in rats</p>
<b>TALC</b>	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.</p> <p>No significant acute toxicological data identified in literature search.</p> <p>The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation.</p> <p>Long-term exposure can also cause a variety of respiratory symptoms.</p> <p>The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>
<b>TITANIUM DIOXIDE</b>	<p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle. It penetrated only the outermost layer of the skin, suggesting that healthy skin may be an effective barrier.</p> <p><b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. * IUCLID</p>
<b>ETHANOL</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
<b>LIMESTONE</b>	Eye (rabbit) 0.75: mg/24h - No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects.
<b>TOLUENE</b>	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>For toluene: <b>Acute Toxicity</b> Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death. Similar effects are observed in short-term animal studies. <b>Humans</b> - Toluene ingestion or inhalation can result in severe central nervous system depression, and in large doses, can act as a narcotic. The ingestion of about 60 mL resulted in fatal nervous system depression within 30 minutes in one reported case.</p>

<b>BUTYL BENZYL PHTHALATE</b>	<p>The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.</p> <p>for butyl benzyl phthalate:</p> <p><b>Repeat dose toxicity:</b> The repeated-dose toxicity of BBP has been well investigated in studies, primarily in the rat, in which dose-response was well characterised. Effects observed consistently have been decreases in body weight gain (often accompanied by decreases in food consumption) and increases in organ to body weight ratios, particularly for the kidney and liver. Histopathological effects on the pancreas and kidney and haematological effects have also been observed. At higher doses, degenerative effects on the testes and, occasionally, histopathological effects on the liver have been reported.</p> <p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).</p> <p>The substance is classified by IARC as Group 3:</p> <p><b>NOT</b> classifiable as to its carcinogenicity to humans.</p> <p>Evidence of carcinogenicity may be inadequate or limited in animal testing.</p> <p>Reproductive effector in rats.</p>
<b>N-BUTYL ACETATE &amp; LIMESTONE</b>	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p>

<b>Acute Toxicity</b>	✔	<b>Carcinogenicity</b>	⊘
<b>Skin Irritation/Corrosion</b>	✔	<b>Reproductivity</b>	✔
<b>Serious Eye Damage/Irritation</b>	✔	<b>STOT - Single Exposure</b>	✔
<b>Respiratory or Skin sensitisation</b>	⊘	<b>STOT - Repeated Exposure</b>	⊘
<b>Mutagenicity</b>	⊘	<b>Aspiration Hazard</b>	⊘

**Legend:** ✖ – Data available but does not fill the criteria for classification  
✔ – Data required to make classification available  
⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
n-butyl acetate	EC50	48	Crustacea	≈32mg/L	1
n-butyl acetate	EC50	96	Algae or other aquatic plants	1.675mg/L	3
n-butyl acetate	EC50	96	Fish	18mg/L	2
n-butyl acetate	LC50	96	Fish	18mg/L	2
n-butyl acetate	NOEC	504	Crustacea	23mg/L	2
acetone	EC50	384	Crustacea	97.013mg/L	3
acetone	EC50	48	Crustacea	>100mg/L	4
acetone	EC50	96	Algae or other aquatic plants	20.565mg/L	4
acetone	LC50	96	Fish	>100mg/L	4
acetone	NOEC	96	Algae or other aquatic plants	4.950mg/L	4
xylene	EC50	24	Crustacea	0.711mg/L	4
xylene	LC50	96	Fish	0.0013404mg/L	4
xylene	EC50	48	Crustacea	>3.4mg/L	2
xylene	EC50	72	Algae or other aquatic plants	4.6mg/L	2
xylene	NOEC	73	Algae or other aquatic plants	0.44mg/L	2
titanium dioxide	LC50	96	Fish	9.214mg/L	3
titanium dioxide	EC50	72	Algae or other aquatic plants	5.83mg/L	4
titanium dioxide	NOEC	336	Fish	0.089mg/L	4
titanium dioxide	EC50	48	Crustacea	1.23mg/L	2
titanium dioxide	EC50	504	Crustacea	0.46mg/L	2
ethanol	EC50	24	Algae or other aquatic plants	0.0129024mg/L	4
ethanol	EC50	48	Crustacea	2mg/L	4
ethanol	LC50	96	Fish	42mg/L	4
ethanol	NOEC	2016	Fish	0.000375mg/L	4
ethanol	EC50	72	Algae or other aquatic plants	275mg/L	2
limestone	LC50	96	Fish	>56000mg/L	4
limestone	EC50	72	Algae or other aquatic plants	>14mg/L	2
limestone	NOEC	72	Algae or other aquatic plants	14mg/L	2
toluene	BCF	24	Algae or other aquatic plants	10mg/L	4
toluene	EC50	3	Algae or other aquatic plants	0.1336030mg/L	4
toluene	EC50	48	Crustacea	0.01151750mg/L	4
toluene	EC50	72	Algae or other aquatic plants	12.5mg/L	4
toluene	LC50	96	Fish	0.0031704mg/L	4
toluene	NOEC	168	Crustacea	0.74mg/L	2

Continued...

## Colorespec Plastic Primer

butyl benzyl phthalate	BCF	78.48	Fish	0.034mg/L	4
butyl benzyl phthalate	EC50	48	Crustacea	0.017mg/L	4
butyl benzyl phthalate	EC50	96	Algae or other aquatic plants	0.1mg/L	4
butyl benzyl phthalate	EC50	96	Algae or other aquatic plants	0.12mg/L	4
butyl benzyl phthalate	NOEC	336	Algae or other aquatic plants	<0.02mg/L	1
butyl benzyl phthalate	LC50	96	Fish	0.51mg/L	2
dimethyl ether	NOEC	48	Crustacea	>4000mg/L	1
dimethyl ether	EC50	384	Crustacea	46.027mg/L	3
dimethyl ether	LC50	96	Fish	200.592mg/L	3
dimethyl ether	EC50	48	Crustacea	>4400.0mg/L	2
dimethyl ether	EC50	96	Algae or other aquatic plants	154.917mg/L	2

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

Atmospheric Fate: PAHs are 'semi-volatile substances' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization.

Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive.

Ecotoxicity - Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus.

Most ethers are very resistant to hydrolysis, and the rate of cleavage of the carbon-oxygen bond by abiotic processes is expected to be insignificant.

Direct photolysis will not be an important removal process since aliphatic ethers do not absorb light at wavelengths >290 nm

For Xylenes:

log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H2O surface water : 24-672; Half-life (hr) H2O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m3 /mol : 637-879; Henry's atm m3 /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.

Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces. The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated.

For Ketones: Ketones, unless they are alpha, beta-unsaturated ketones, can be considered as narcosis or baseline toxicity compounds.

Aquatic Fate: Hydrolysis of ketones in water is thermodynamically favourable only for low molecular weight ketones. Reactions with water are reversible with no permanent change in the structure of the ketone substrate. Ketones are stable to water under ambient environmental conditions.

**DO NOT discharge into sewer or waterways.**

For n-Butyl Acetate:

Koc: ~200;

log Kow: 1.78;

Half-life (hr) air: 144;

Half-life (hr) H2O surface water: 178 - 27156;

Henry's atm: m3 /mol: 3.20E-04

BOD 5 if unstated: 0.15-1.02,7%;

COD: 78%;

ThOD: 2.207;

BCF : 4-14.

Environmental Fate: Terrestrial Fate - Butyl acetate is expected to have moderate mobility in soil. Volatilization of n-butyl acetate is expected from moist and dry soil surfaces. n-Butyl acetate may biodegrade in soil.

For Acetone:

log Kow : -0.24;

Half-life (hr) air : 312-1896;

Half-life (hr) H2O surface water : 20;

Henry's atm m3 /mol : 3.67E-05

BOD 5: 0.31-1.76,46-55%

COD: 1.12-2.07

ThOD: 2.2BCF: 0.69.

Environmental Fate: The relatively long half-life allows acetone to be transported long distances from its emission source.

Atmospheric Fate: Acetone preferentially locates in the air compartment when released to the environment. In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-butyl acetate	LOW	LOW
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
titanium dioxide	HIGH	HIGH
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
butyl benzyl phthalate	HIGH (Half-life = 180 days)	LOW (Half-life = 2.5 days)
dimethyl ether	LOW	LOW

### Bioaccumulative potential

Ingredient	Bioaccumulation
n-butyl acetate	LOW (BCF = 14)
acetone	LOW (BCF = 0.69)

xylene	MEDIUM (BCF = 740)
titanium dioxide	LOW (BCF = 10)
ethanol	LOW (LogKOW = -0.31)
toluene	LOW (BCF = 90)
butyl benzyl phthalate	MEDIUM (BCF = 663)
dimethyl ether	LOW (LogKOW = 0.1)

**Mobility in soil**

Ingredient	Mobility
n-butyl acetate	LOW (KOC = 20.86)
acetone	HIGH (KOC = 1.981)
titanium dioxide	LOW (KOC = 23.74)
ethanol	HIGH (KOC = 1)
toluene	LOW (KOC = 268)
butyl benzyl phthalate	LOW (KOC = 9359)
dimethyl ether	HIGH (KOC = 1.292)

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Product / Packaging disposal</b>	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> </ul>
-------------------------------------	---

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

	
<b>Marine Pollutant</b>	NO
<b>HAZCHEM</b>	Not Applicable

**Land transport (ADG)**

<b>UN number</b>	1950				
<b>Packing group</b>	Not Applicable				
<b>UN proper shipping name</b>	AEROSOLS				
<b>Environmental hazard</b>	Not Applicable				
<b>Transport hazard class(es)</b>	<table style="width: 100%; border: none;"> <tr> <td style="border: none;">Class</td> <td style="border: none;">2.1</td> </tr> <tr> <td style="border: none;">Subrisk</td> <td style="border: none;">Not Applicable</td> </tr> </table>	Class	2.1	Subrisk	Not Applicable
Class	2.1				
Subrisk	Not Applicable				
<b>Special precautions for user</b>	<table style="width: 100%; border: none;"> <tr> <td style="border: none;">Special provisions</td> <td style="border: none;">63 190 277 327 344</td> </tr> <tr> <td style="border: none;">Limited quantity</td> <td style="border: none;">1000ml</td> </tr> </table>	Special provisions	63 190 277 327 344	Limited quantity	1000ml
Special provisions	63 190 277 327 344				
Limited quantity	1000ml				

**Air transport (ICAO-IATA / DGR)**

<b>UN number</b>	1950
<b>Packing group</b>	Not Applicable
<b>UN proper shipping name</b>	Aerosols, flammable; Aerosols, flammable (engine starting fluid)
<b>Environmental hazard</b>	Not Applicable

<b>Transport hazard class(es)</b>	ICAO/IATA Class	2.1
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	10L
<b>Special precautions for user</b>	Special provisions	A145A167A802; A1A145A167A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203; Forbidden
	Passenger and Cargo Maximum Qty / Pack	75 kg; Forbidden
	Passenger and Cargo Limited Quantity Packing Instructions	Y203; Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G; Forbidden

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1950	
<b>Packing group</b>	Not Applicable	
<b>UN proper shipping name</b>	AEROSOLS	
<b>Environmental hazard</b>	Not Applicable	
<b>Transport hazard class(es)</b>	IMDG Class	2.1
	IMDG Subrisk	Not Applicable
<b>Special precautions for user</b>	EMS Number	F-D, S-U
	Special provisions	63 190 277 327 344 959
	Limited Quantities	1000ml

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****N-BUTYL ACETATE(123-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**ACETONE(67-64-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**XYLENE(1330-20-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**TALC(14807-96-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

**LIMESTONE(1317-65-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

**TOLUENE(108-88-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**BUTYL BENZYL PHTHALATE(85-68-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**DIMETHYL ETHER(115-10-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Continued...

Australia Exposure Standards  
Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)  
International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List  
Passenger and Cargo Aircraft

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (toluene; talc; acetone; xylene; n-butyl acetate; dimethyl ether; ethanol; butyl benzyl phthalate)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (butyl benzyl phthalate)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
<b>Legend:</b>	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
titanium dioxide	100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12188-41-9, 12701-76-7, 12767-65-6, 12789-63-8, 1309-63-3, 1317-70-0, 1317-80-2, 1344-29-2, 13463-67-7, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9
dimethyl ether	115-10-6, 157621-61-9

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC— TWA: Permissible Concentration-Time Weighted Average  
 PC— STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.